

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)

Other means of identification:

UFI: 6EH0-K03S-X00Y-5CVY

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Varnish

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A. Barrio Sakoni, 10

48950 ERANDIO - Vizcaya - España

Phone: +34 944 670 062 - Fax: +34 944 675 832

laboratorio@juno.es www.juno.es

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

 ${\tt P304+P340: IF\ INHALED: Remove\ person\ to\ fresh\ air\ and\ keep\ comfortable\ for\ breathing.}$

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

Additional Labelling:

As from 24 August 2023 adequate training is required before industrial or professional use.

UFI: 6EH0-K03S-X00Y-5CVY

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 1/14** (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous mixture composed of additives, aggregates and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification			
	28182-81-2	Hexamethylene diiso	ocyanate, oligomers ⁽¹⁾	Self-classified		
EC: Index: REACH:	931-274-8 Non-applicable 01-2119485796-17- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	(1)	75 - <100 %	
CAS:	98-94-2	Cyclohexyldimethyla	mine ⁽¹⁾	Self-classified		
EC: Index: REACH:	202-715-5 Non-applicable 01-2119533030-60- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Aquatic Chronic 3: H412; Flam. Liq. 3: H226; Skin Corr. 1B: H314 - Danger		1 - <2,5 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Cyclohexyldimethylamine	LD50 oral	289 mg/kg	Rat
CAS: 98-94-2	LD50 dermal	380 mg/kg	Rat
EC: 202-715-5	LC50 inhalation	3 mg/L (ATEi)	
Hexamethylene diisocyanate, oligomers	LD50 oral	Not relevant	
CAS: 28182-81-2	LD50 dermal	Not relevant	
EC: 931-274-8	LC50 inhalation	11 mg/L (ATEi)	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 2/14** (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 3/14** (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 7: HANDLING AND STORAGE (continued)

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short	exposure	xposure Long exposure	
Identification		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 28182-81-2	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 931-274-8	Inhalation	Not relevant	1 mg/m³	Not relevant	0,5 mg/m ³
Cyclohexyldimethylamine	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 98-94-2	Dermal	Not relevant	Not relevant	0,6 mg/kg	Not relevant
EC: 202-715-5	Inhalation	Not relevant	8,3 mg/m ³	0,53 mg/m ³	8,3 mg/m ³

DNEL (General population):

Not relevant

PNEC:

Identification				
Hexamethylene diisocyanate, oligomers	STP	88 mg/L	Fresh water	0,127 mg/L
CAS: 28182-81-2	Soil	53183 mg/kg	Marine water	0,013 mg/L
EC: 931-274-8	Intermittent	1,27 mg/L	Sediment (Fresh water)	266701 mg/kg
	Oral	Not relevant	Sediment (Marine water)	26670 mg/kg
Cyclohexyldimethylamine	STP	20,6 mg/L	Fresh water	0,002 mg/L
CAS: 98-94-2	Soil	0,003 mg/kg	Marine water	0 mg/L
EC: 202-715-5	Intermittent	0,02 mg/L	Sediment (Fresh water)	0,021 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,002 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 4/14** (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CAT III	EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks	
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.	

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	**	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 1,6 % weight

V.O.C. density at 20 °C: 17,44 kg/m³ (17,44 g/L)

Average carbon number: 8

Average molecular weight: 127,2 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 17,44 kg/m³ (17,44 g/L)

EU limit for the product (Cat. A.J): 140 g/L (2010)

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 5/14** (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Components: Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colourless

Odour:

Characteristic

Odour threshold:

Not relevant *

Volatility:

Boiling point at atmospheric pressure: 165 °C Vapour pressure at 20 °C: 160 Pa

Vapour pressure at 50 °C: 1151,3 Pa (1,15 kPa) Evaporation rate at 20 °C: Not relevant *

Product description:

Density at 20 °C: 1040 - 1140 kg/m³

Relative density at 20 °C: 1,04 - 1,14 Dynamic viscosity at 20 °C: 1200 cP Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: >20,5 mm²/s Concentration: Not relevant * pH: Not relevant * Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant *

Solubility properties: Soluble in organic solvents

Decomposition temperature:

Melting point/freezing point:

Not relevant *

Not relevant *

Flammability:

Flash Point: 40 °C

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Not relevant *

Not relevant *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Not relevant *


Corrosive to metals:

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 6/14** (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Heat of combustion: Not relevant *

Aerosols-total percentage (by mass) of flammable Not relevant *

components:

Other safety characteristics:

Surface tension at 20 °C:

Not relevant *

Refraction index:

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 7/14** (Replaced 7)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

 IARC: Not relevant
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acu	Acute toxicity		
Cyclohexyldimethylamine	LD50 oral	289 mg/kg (ATEi)	Rat	
CAS: 98-94-2	LD50 dermal	380 mg/kg (ATEi)	Rat	
EC: 202-715-5	LC50 inhalation	3 mg/L (ATEi)		
Hexamethylene diisocyanate, oligomers	LD50 oral	5100 mg/kg	Rat	
CAS: 28182-81-2	LD50 dermal			
EC: 931-274-8	LC50 inhalation	11 mg/L (ATEi)		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Hexamethylene diisocyanate, oligomers	LC50	Not relevant		
CAS: 28182-81-2	EC50	Not relevant		
EC: 931-274-8	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 (Replaced 7)

Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 8/14**





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Cyclohexyldimethylamine	LC50	28 mg/L (96 h)	Leuciscus idus	Fish
CAS: 98-94-2	EC50 75 mg/L (48 h) Daphnia magna		Daphnia magna	Crustacean
EC: 202-715-5	EC50	2 mg/L (72 h)	Desmodesmus subspicatus	Algae

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Cyclohexyldimethylamine	BOD5	Not relevant	Concentration	20 mg/L
CAS: 98-94-2	COD	Not relevant	Period	28 days
EC: 202-715-5	BOD5/COD	Not relevant	% Biodegradable	95 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Cyclohexyldimethylamine	BCF	
CAS: 98-94-2	Pow Log	2.31
EC: 202-715-5	Potential	

12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		Volatility	
Cyclohexyldimethylamine	Koc	69.49	Henry	6,73 Pa·m³/mol	
CAS: 98-94-2	Conclusion	High	Dry soil	Not relevant	
EC: 202-715-5	Surface tension	Not relevant	Moist soil	Not relevant	

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous	

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 9/14** (Replaced 7)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 14: TRANSPORT INFORMATION (continued)



UN1263 14.1 UN number or ID number: 14.2 UN proper shipping name: **PAINT** 14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: III 14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 163, 367, 650

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 I

14.7 Maritime transport in bulk according to IMO instruments:

Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

14.1 UN number or ID number: UN1992

14.2 UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (Cyclohexyldimethylamine;

Hexamethylene-di-isocyanate)

14.3 Transport hazard class(es):

Labels: 3, 6.1

14.4 Packing group: III14.5 Marine pollutant: Nο

14.6 Special precautions for user

Special regulations: 274, 223 EmS Codes: F-E, S-D Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Not relevant 14.7 Maritime transport in bulk Not relevant

according to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number or ID number: UN1992

14.2 UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (Cyclohexyldimethylamine;

Hexamethylene-di-isocyanate)

14.3 Transport hazard class(es):

Labels: 3, 6.1

14.4 Packing group: III 14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9 14.7 Maritime transport in bulk

according to IMO

instruments:

Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 Page 10/14 (Replaced 7)





BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 15: REGULATORY INFORMATION (continued)

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 11/14** (Replaced 7)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

- (a) the concentration of diisocyanates individually and in combination is less than 0.1 % by weight, or (b) the employer or selfemployed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).
- 2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:
- (a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".
- 3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.
- 4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:
- (a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).
- (b) the training elements in points (a) and (b) of paragraph 5 for the following uses:
- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route
- (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:
- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or

inhalation route.

- 5. Training elements:
- (a) general training, including on-line training, on:
- chemistry of diisocvanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 Page 12/14 (Replaced 7)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



SECTION 15: REGULATORY INFORMATION (continued)

- certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
- additional behaviour-based aspects
- maintenance
- management of change
- evaluation of existing safety instructions
- risk in relation to application process used
- certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed
- 6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture (s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.
- 7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.
- 8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.
- 9. Member States shall include in their reports pursuant to Article 117(1) the following information:
- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
- (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.
- 10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H332: Harmful if inhaled.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

Printing: 27/06/2024 Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8 **Page 13/14** (Replaced 7)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BNZ AQUAPUR BRILLO 2/C COMP B - Código - 82485 (B)



Page 14/14

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Acute Tox. 4: Calculation method Skin Sens. 1: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50

EC50: Lethal Concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Date of compilation: 13/06/2017 Revised: 27/04/2023 Version: 8

Printing: 27/06/2024 (Replaced 7)