

JUNO

PAINT MANUFACTURERS SINCE 1927

March
2024

Product Catalogue

Professional and
decorative paints
and coatings.

**DECORATION
CONSTRUCTION
RESTORATION**



Due to limitations with the printing process, colour swatches and images are for inspiration purposes only. The colour swatches do not exactly match the paint colour in the can. Colour chips in product colour cards will be much more accurate, but slight variations between batches of paint may occur.

Where more than one tin of paint is required, check that batch numbers are identical, and if not, intermix before use.

Please ensure a tester is used on the actual surface to be painted before decoration.

This catalogue and the images and information herein is the property of JUNO and may not be copied or reproduced without the express authorisation of JUNO. Unauthorised reproduction is protected by law. Any consultation and authorisation to use this catalogue must be sent to JUNO (export@juno.es).

INDEX

EXTERIOR

Exterior house paint and masonry surfaces	5
High Build masonry coatings	7
Acrylic renders	8
Specialist exterior coatings	9
Exterior sealers & primers	10
Hydrophobic treatment	10

WATERPROOFING

Horizontal waterproofing	12
Façades & vertical waterproofing	13

INTERIOR

Interior emulsions	15
Trade emulsions ideal for spraying	16
Specialist interior paints	16
AENOR certified washable paints	17
Interior tinting bases	17
Sealers	18
Stainblocks	18

FLOOR COATINGS

1K Floor coatings	20
2K Floor coatings	20
100% Solids 2K Epoxy system	22
Pool/Milking parlour/Traffic Marking	22
Line marking for grass/turf	22

TRIM PAINT

Solvent-based enamels	24
Water-based enamels	26
Tinting bases - Decorative	27
Tinting bases - Industrial	27
Adhesion & anti-corrosive primers	28
Wood primers	28

WOOD COATINGS

Undercoat and preparation	30
Water-based enamels	30
Solvent-based enamels	31

SUNDRIES

Fillers & caulk	33
Colourants, paint stripper, additives, etc	34
Thinners & cleaners	36
Colour charts & fan decks	36

SUPPLEMENTARY PRODUCTS

Special exterior coatings	38
Special interior coatings	39
Water-based 2K polyurethane	40
Sealers/primers	40
Thinners	40
2K Clear polyurethanes	41
Colourants - Tinting System	41

MARKETED PRODUCT RANGE

Intumescent paints	43
Waterproofing:	
Liquid polyurethane membrane	43



EXTERIOR

- _ Exterior house paint and masonry surfaces
- _ High Build masonry coatings
- _ Acrylic renders
- _ Specialist exterior coatings
- _ Exterior sealers and primers
- _ Hydrophobic treatment

Exterior house paint and masonry surfaces

NOVOKRIL

Satin



Matt



JUNO Façades Colour CARD
JUNOMATIC Tinting System

Premium performance microporous and breathable masonry coating. With anti-mould protection.

100% pure acrylic resin, formulated with advanced technology pure acrylic copolymers for great flexibility and adhesion that make it resistant to rain water and permeable to water vapour, allowing moisture and air to be released.

For exterior use.

Cleaning and dilution with water.



Recommended for decorating and waterproofing masonry surfaces such as cement and concrete materials (façades, walls, patios, etc.) and any surface that requires maximum resistance to atmospheric agents and humid environments.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.



Satin finish

15 l

4 l

White base/P (62.150)

Medium base/D (62.169)

Deep base/TR (62.170)

Matt finish

15 l

4 l

White base/P (62.195)

Medium base/D (62.145)

Deep base/TR (62.146)

JUNOKRIL

Satin



Matt



JUNO Façades Colour CARD
JUNOKRIL Colour CARD
JUNOMATIC Tinting System

High performance microporous and breathable paint. With anti-mould protection..

Formulated with acrylic-vinyl copolymers (satin finish) or pure acrylic resins (matt finish) with anti-carbonation properties. Resistant to rain water and permeable to water vapours, allowing moisture and air to be released. Wide range of tinting bases for optimal performance, colour stability and opacity.

For exterior use.

Recommended for decorating and waterproofing masonry surfaces such as cement and concrete materials (façades, walls, patios, etc.) and any surface that requires maximum resistance to atmospheric agents and humid environments.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE Certified: Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.



Satin finish

15 l

4 l

750 ml

White base/P (61.000)

Black* (61.001)

Ochre* (61.065)

Turkish red* (61.070)

Txoko brown* (61.071)

Pelota court green* (61.052)

Blue* (61.012)

Red* (61.016)

Yellow* (61.025)

Medium base/D (61.195)

Deep base/TR (61.196)

Matt finish

15 l

4 l

750 ml





























White base/P (60.500)

Medium base/D (60.501)



Deep base/TR (60.502)

Yellow base/GL* (88.895)






Red base/ RD* (88.896)

<p>BIKRIL <i>Satin</i></p>  <p><i>Silk</i></p>  <p><i>Matt</i></p>   <p>JUNO Façades Colour CARD</p> <p>BIKRIL/LUNA Colour CARD</p> <p>JUNOMATIC Tinting System</p>	<p>High quality microporous and breathable water-based paint, special for decoration. With anti-mould protection.</p> <p>Formulated with high quality resins, with anti-carbonation properties. Quick drying formulation resistant to rain water and permeable to water vapour allowing moisture and air to be released. For exterior and interior use.</p> <p>Cleaning and dilution with water.</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p>Satin finish</p> <p><input type="checkbox"/> White base/P (60.100)</p> <p> Medium base/D (60.101)</p> <p> Deep base/TR (60.102)</p> <p>Silk finish</p> <p><input type="checkbox"/> White base/P (60.400)</p> <p> Medium base/D (60.401)</p> <p> Deep base/TR (60.402)</p> <p>Matt finish</p> <p><input type="checkbox"/> White base/P (60.300)</p> <p> Medium base/D (60.301)</p> <p> Deep base/TR (60.302)</p>	<p>Recommended for decorating and waterproofing masonry surfaces such as cement and concrete materials. Also ideal for kitchens, bathrooms and other areas exposed to contact with water, humidity, etc.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE (only matt finish): Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.</p> <p>    </p> <p>15 l 4 l 750 ml</p> <p>15 l 4 l 750 ml</p> <p>15 l 4 l 750 ml</p>
<p>J-300 <i>High Satin</i></p> 	<p>High satin finish emulsion. With anti-mould protection.</p> <p>Formulated in dispersion using Veova vinyl resins. For exterior and interior use.</p> <p>Cleaning and dilution with water.</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (71.055)</p>	<p>Recommended for general use in construction on plaster, cement surfaces, etc. Good whiteness, hiding power and easy application. Resistant to wet rubbing and scuffing and permeable to water vapour, allowing moisture and air to be released.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p> <p></p> <p>15 l 4 l</p>
<p>J-3000 <i>Medium Satin</i></p> 	<p>Medium satin finish emulsion. With anti-mould protection.</p> <p>Formulated with resins in aqueous dispersion. For exterior and interior use.</p> <p>Cleaning and dilution with water.</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (71.063)</p>	<p>Recommended for general use in construction on plaster, cement surfaces, etc. Good whiteness, hiding power and easy application. Resistant to wet rubbing and scuffing and permeable to water vapour, allowing moisture and air to be released.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p> <p></p> <p>15 l 4 l</p>
<p>A-100 STIMAX <i>Matt</i></p> 	<p>High performance water-based acrylic paint. With anti-mould protection.</p> <p>Formulated with 100% acrylic resins in aqueous dispersion, titanium dioxide and extenders. For exterior and interior use. Cleaning and dilution with water.</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (62.400)</p>	<p>Recommended for decorating façades, walls and for interiors and spaces where a quality matt finish, resistant to water and permeable to water vapour is required, allowing moisture and air to be released.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p> <p></p> <p>15 l 4 l 750 ml</p>
<p>A-5000 <i>Matt</i></p> 	<p>High performance exterior trade masonry paint. With anti-mould protection.</p> <p>Formulated with styrene-acrylic resins in aqueous dispersion. Excellent value for money. For exterior and interior use. Cleaning and dilution with water.</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (62.590)</p>	<p>Recommended for decorating façades, patios, warehouses and places where an optimal finish at an economical price is required.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p> <p></p> <p>15 l 4 l</p>

High Build masonry coatings

<p>SUPER JUNOREV Matt / Smooth</p>  <p>JUNO Façades Colour CARD JUNOMATIC Tinting System</p>	<p>Premium high build masonry coating. With anti-mould protection.</p> <p>Formulated with the highest quality acrylic copolymers in aqueous dispersion providing excellent outdoor performance. Super Junorev is microporous and breathable allowing moisture and air to be released. For exterior and interior use. Cleaning and dilution with water.</p> <p>EPD THE INTERNATIONAL EPD SYSTEM</p> <p>Smooth finish</p> <p><input type="checkbox"/> White base/P (65.101)</p> <p><input checked="" type="checkbox"/> Medium base/D (65.215)</p> <p><input checked="" type="checkbox"/> Deep base/TR (65.216)</p>	<p>Recommended for protecting and decorating mineral surfaces, including renders and pebbledash, in need of protection from rain, humidity, micro-organisms and carbonation. Super Junorev actively resists peeling and flaking.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE (Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.</i></p> <p>CE ADHESION PERMEABILITY ANTI-CARBONATION FIRE RETARDANT B-s1,d0</p> <p>15 l 4 l</p>																		
<p>JUNOREV Matt / Smooth</p>  <p>Matt / Textured</p>  <p>JUNO Façades Colour CARD JUNOREV Colour CARD</p>	<p>100% acrylic high build masonry coating. With anti-mould protection.</p> <p>Formulated with acrylic resins in aqueous dispersion with excellent mechanical properties. Junorev is both microporous and breathable allowing moisture and air to be released. For exterior and interior use. Cleaning and dilution with water.</p> <p>EPD THE INTERNATIONAL EPD SYSTEM</p> <p>Smooth finish</p> <p><input type="checkbox"/> White base/P (65.500)</p> <table border="0"> <tr> <td><input checked="" type="checkbox"/> Grey* (65.502)</td> <td><input checked="" type="checkbox"/> Brick* (65.547)</td> <td><input checked="" type="checkbox"/> Pastel* (65.580)</td> </tr> <tr> <td><input checked="" type="checkbox"/> Clay* (65.515)</td> <td><input checked="" type="checkbox"/> Terracotta* (65.548)</td> <td><input checked="" type="checkbox"/> Cinnamon* (65.582)</td> </tr> <tr> <td><input checked="" type="checkbox"/> Sand* (65.521)</td> <td><input checked="" type="checkbox"/> Light beige* (65.560)</td> <td><input checked="" type="checkbox"/> Hazelnut* (65.584)</td> </tr> <tr> <td><input checked="" type="checkbox"/> Cream* (65.522)</td> <td><input checked="" type="checkbox"/> Turkish red* (65.570)</td> <td><input checked="" type="checkbox"/> Dune* (65.585)</td> </tr> <tr> <td><input checked="" type="checkbox"/> Wheat yellow* (65.530)</td> <td><input checked="" type="checkbox"/> Tile* (65.575)</td> <td></td> </tr> <tr> <td><input checked="" type="checkbox"/> Mustard yellow* (65.550)</td> <td><input checked="" type="checkbox"/> Pelota court green* (65.552)</td> <td></td> </tr> </table> <p>Textured Finish</p> <p><input type="checkbox"/> White base/P (64.500)</p>	<input checked="" type="checkbox"/> Grey* (65.502)	<input checked="" type="checkbox"/> Brick* (65.547)	<input checked="" type="checkbox"/> Pastel* (65.580)	<input checked="" type="checkbox"/> Clay* (65.515)	<input checked="" type="checkbox"/> Terracotta* (65.548)	<input checked="" type="checkbox"/> Cinnamon* (65.582)	<input checked="" type="checkbox"/> Sand* (65.521)	<input checked="" type="checkbox"/> Light beige* (65.560)	<input checked="" type="checkbox"/> Hazelnut* (65.584)	<input checked="" type="checkbox"/> Cream* (65.522)	<input checked="" type="checkbox"/> Turkish red* (65.570)	<input checked="" type="checkbox"/> Dune* (65.585)	<input checked="" type="checkbox"/> Wheat yellow* (65.530)	<input checked="" type="checkbox"/> Tile* (65.575)		<input checked="" type="checkbox"/> Mustard yellow* (65.550)	<input checked="" type="checkbox"/> Pelota court green* (65.552)		<p>Recommended for protecting and decorating mineral surfaces, including renders and pebbledash, in need of protection from rain, humidity, micro-organisms and carbonation. Junorev actively resists peeling and flaking.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE (smooth finish): Direct pull-off adhesion - Anti-carbonation - Light Stability - Permeability to rain water and water vapour - Fire retardant to B-s1,d0 standard.</i></p> <p>CE ADHESION PERMEABILITY ANTI-CARBONATION LIGHT STABILITY FIRE RETARDANT B-s1,d0</p> <p>15 l 4 l</p> <p>NA</p>
<input checked="" type="checkbox"/> Grey* (65.502)	<input checked="" type="checkbox"/> Brick* (65.547)	<input checked="" type="checkbox"/> Pastel* (65.580)																		
<input checked="" type="checkbox"/> Clay* (65.515)	<input checked="" type="checkbox"/> Terracotta* (65.548)	<input checked="" type="checkbox"/> Cinnamon* (65.582)																		
<input checked="" type="checkbox"/> Sand* (65.521)	<input checked="" type="checkbox"/> Light beige* (65.560)	<input checked="" type="checkbox"/> Hazelnut* (65.584)																		
<input checked="" type="checkbox"/> Cream* (65.522)	<input checked="" type="checkbox"/> Turkish red* (65.570)	<input checked="" type="checkbox"/> Dune* (65.585)																		
<input checked="" type="checkbox"/> Wheat yellow* (65.530)	<input checked="" type="checkbox"/> Tile* (65.575)																			
<input checked="" type="checkbox"/> Mustard yellow* (65.550)	<input checked="" type="checkbox"/> Pelota court green* (65.552)																			
<p>LUNA Matt</p>  <p>BIKRIL/LUNA Colour CARD JUNOMATIC Tinting System</p>	<p>High build masonry coating with anti-mould protection.</p> <p>Formulated with styrene-acrylic resins in aqueous dispersion with excellent mechanical properties and permeable to water vapour, allowing moisture and air to be released. For exterior and interior use. Cleaning and dilution with water.</p> <p>EPD THE INTERNATIONAL EPD SYSTEM</p> <p>White base/P (67.500)</p> <p><input checked="" type="checkbox"/> Deep base/TR (67.501)</p>	<p>Recommended for the protection and decoration of mineral surfaces (cement, concrete, pebbledash or renders, etc.). Ideal for correcting finishing faults and touch-ups on surfaces, providing a high opacity decorative finish.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p>FIRE RETARDANT B-s1,d0</p> <p>15 l</p>																		




Acrylic renders

<p>EVOKRIL BASE Matt</p>  <p>JUNO Façades Colour CARD</p>	<p>Water-based pigmented acrylic copolymer primer base coating for the EVOKRIL decorative/protective render system, ETICS system - JUNOTherm® and other masonry systems.</p> <p>Formulated based on water-based acrylic copolymers to consolidate, waterproof and even out the surface before applying the render. Fine-grained. Great penetrating power.</p> <p>Excellent waterproofing and breathability.</p> <p>For interior and exterior use.</p> <p>Cleaning and thinning with water.</p> <p><input type="checkbox"/> White base/P (64.400)</p> <p><input checked="" type="checkbox"/> Deep base/TR (64.401)</p>	<p>Recommended as a primer on surfaces such as paint, cement, fibre cement, plaster, concrete, non-waterproof surfaces, etc. for EVOKRIL render system and other masonry coatings.</p> <p>Improves adhesion and uniformity of successive paint coats.</p> <p style="text-align: right;">22 kg</p>															
<p>EVOKRIL Matt</p>  <p>JUNO Façades Colour CARD</p>	<p>Acrylic render for waterproofing and decorating facades. (0.7 mm grain size) With anti-mould protection.</p> <p>Formulated based on acrylic copolymers and selected fillers to achieve a variety of decorative finishes and textures: dropfinish, floated, roughcast and scraped finish.</p> <p>Great elasticity, adhesion and hardness.</p> <p>Excellent waterproofing capacity and breathability.</p> <p>For interior and exterior use.</p> <p>Cleaning and thinning with water.</p> <p><input type="checkbox"/> White base/P</p> <p><input checked="" type="checkbox"/> Deep base/TR</p>	<p>Recommended to achieve decorative finishes on facades. For universal application on non-waterproof concrete, cement, plaster, fiber cement, paint, etc.</p> <p>Finishing mortar for ETICS JUNOTherm® system.</p> <p><i>APPROVAL CERTIFICATES: CE certified for Direct traction adhesion - Permeability to rainwater and water vapours.</i></p> <div style="text-align: right;">  <table border="1" style="display: inline-table; margin-left: 10px;"> <tr> <td style="padding: 2px;">ADHESION</td> <td style="padding: 2px;">PERMEABILITY</td> <td style="padding: 2px;">FIRE RETARDANT B-s2,d0</td> </tr> </table> </div> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 5px;">25 kg:</th> <th style="text-align: left; padding: 5px;">Grain 0,7</th> <th style="text-align: left; padding: 5px;">Grain 1,0</th> <th style="text-align: left; padding: 5px;">Grain 1,5</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;"><input type="checkbox"/> White base/P</td> <td style="padding: 5px;">(64.408)</td> <td style="padding: 5px;">(64.424)</td> <td style="padding: 5px;">(64.416)</td> </tr> <tr> <td style="padding: 5px;"><input checked="" type="checkbox"/> Deep base/TR</td> <td style="padding: 5px;">(64.409)</td> <td style="padding: 5px;">(64.425)</td> <td style="padding: 5px;">(64.417)</td> </tr> </tbody> </table>	ADHESION	PERMEABILITY	FIRE RETARDANT B-s2,d0	25 kg:	Grain 0,7	Grain 1,0	Grain 1,5	<input type="checkbox"/> White base/P	(64.408)	(64.424)	(64.416)	<input checked="" type="checkbox"/> Deep base/TR	(64.409)	(64.425)	(64.417)
ADHESION	PERMEABILITY	FIRE RETARDANT B-s2,d0															
25 kg:	Grain 0,7	Grain 1,0	Grain 1,5														
<input type="checkbox"/> White base/P	(64.408)	(64.424)	(64.416)														
<input checked="" type="checkbox"/> Deep base/TR	(64.409)	(64.425)	(64.417)														
<p>EVOKRIL SLX Matt</p>  <p>JUNO Façades Colour CARD</p>	<p>Siloxane-based render (1.5 mm grain size) for decoration and waterproofing exterior walls. With anti-mould protection.</p> <p>Formulated with modified acrylic copolymers with polysiloxanes and selected fillers to achieve a variety of decorative finishes and textures: f.ex. dropfinish, floated, roughcast scraped finish etc.</p> <p>Great elasticity, adhesion and hardness.</p> <p>Repels water and dirt.</p> <p>Excellent waterproofing capacity and breathability. For interior and exterior use.</p> <p>Cleaning and thinning with water.</p> <p><input type="checkbox"/> White base/P</p> <p><input checked="" type="checkbox"/> Deep base/TR</p>	<p>Recommended to achieve decorative finishes on facades. For universal application on non-waterproof concrete, cement, plaster, fiber cement, paint, etc.</p> <p>Finishing mortar for ETICS JUNOTherm® system.</p> <p><i>APPROVAL CERTIFICATES: CE certified for Direct traction adhesion - Permeability to rainwater and water vapours. Fire retardant to Euroclass B-s2,d0.</i></p> <div style="text-align: right;">  <table border="1" style="display: inline-table; margin-left: 10px;"> <tr> <td style="padding: 2px;">ADHESION</td> <td style="padding: 2px;">PERMEABILITY</td> <td style="padding: 2px;">FIRE RETARDANT B-s2,d0</td> </tr> </table> </div> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 5px;">25 kg:</th> <th style="text-align: left; padding: 5px;">Grain 1,5</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;"><input type="checkbox"/> White base/P</td> <td style="padding: 5px;">(64.440)</td> </tr> <tr> <td style="padding: 5px;"><input checked="" type="checkbox"/> Deep base/TR</td> <td style="padding: 5px;">(64.441)</td> </tr> </tbody> </table>	ADHESION	PERMEABILITY	FIRE RETARDANT B-s2,d0	25 kg:	Grain 1,5	<input type="checkbox"/> White base/P	(64.440)	<input checked="" type="checkbox"/> Deep base/TR	(64.441)						
ADHESION	PERMEABILITY	FIRE RETARDANT B-s2,d0															
25 kg:	Grain 1,5																
<input type="checkbox"/> White base/P	(64.440)																
<input checked="" type="checkbox"/> Deep base/TR	(64.441)																





Specialist exterior coatings

Silicate & Mineral Paint System




<p>MINERAL PRIMER Matt</p> 	<p>Water-based mineral primer based on potassium silicate with excellent penetration and adhesion properties. For interior and exterior use. Cleaning and dilution with water.</p>	<p>Recommended as a base coat in silicate paint systems that require binding, including protecting mineral surfaces such as lime and cement renders, gypsum plasters and stonework. Its also ideal for problematic areas such as damp basements and can also be used as a stabilising primer for powdery and friable surfaces. For a high quality breathable paint system Silicato-Silicate Paint (75.362) is recommended as a topcoat.</p> <p style="text-align: right;">15 l</p>
<p>SILICATO Matt</p>  <p>JUNO Façades Colour CARD</p>	<p>Highly breathable silicate paint. A matt, durable and highly breathable alternative to conventional masonry paints and limewash. Formulated with potassium silicate, fillers, additives and inorganic pigments stable to light and weather. Chemically bonds to create a water/weather-resistant barrier. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p>	<p>Suitable for use on stone, masonry, concrete, pebble dash, plaster and silicate paint surfaces. Perfect match for heritage projects and old buildings.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - A+ Certified for clean interior environment - Meets health related evaluation procedure for emissions of VOC's (German AgBB 2018) - Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l 4 l</p>

Exterior Pliolite paint


<p>JUNOLITE FAÇADES Matt</p>  <p>JUNO Façades Colour CARD</p>	<p>Self-cleaning, breathable Pliolite® paint. Junolite is a premium quality, solvent-based masonry paint formulated for exterior use. Formulated with Pliolite® resins and organic solvents. Offers protection against alkalis and salt efflorescence. For exterior use. Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p>	<p>Junolite provides a long lasting coating with good adhesion and resistance to moisture and alkali attack on exterior surfaces such as cement rendering, rough cast, brick and concrete.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">15 l</p>
---	---	--



Exterior sealers & primers

<p>HIDROCRIL Semi-matt</p> 	<p>Water-based acrylic sealer concentrate providing excellent penetration and adhesion. For interior and exterior use. Cleaning and dilution with water. Mixing ratio 4:1 (Water / Hidrocril).</p>	<p>Hidrocril evens out surface absorption. Recommended as a sealer for surfaces that have problems with adhesion (pearlite, concrete, plaster, cement, asbestos cement, brick), or require binding (tempera, lime, whitewash or unconsolidated paints).</p>
		20 l 4 l 750 ml
<input checked="" type="checkbox"/> Clear (81.006)		
<p>AKRIL - 80 Semi-matt</p> 	<p>Solvent-based acrylic sealer concentrate. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012). Mixing ratio 1:1 (D-16 / Akril-80).</p>	<p>Akril-80 evens out surface absorption. Recommended for sealing surfaces and strengthening damaged or absorbent surfaces (plaster, stone, cement, concrete, old paint, etc.).</p>
		15 l 4 l 750 ml
<input checked="" type="checkbox"/> Clear (42.115)		
<p>PRIMERLITE Matt</p> 	<p>Solvent-based primer based on Pliolite resins. For interior and exterior use. Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).</p>	<p>Recommended as a primer for cement and concrete surfaces where a permeable system of the highest quality is required. Its resistance to alkalis and high penetration power stand out. Primerlite is the primer of choice for JUNO's Exterior paint systems, and is often prescribed for use with Novokril, Junokril, Bikril, etc.</p>
		15 l 4 l
<input type="checkbox"/> White (21.702)		

Hydrophobic treatment




<p>SILOXANE SEALER</p> 	<p>Solvent-based protection for porous mineral surfaces. Formulated with polysiloxane compounds as a hydrophobic impregnation to reduce the absorption of rainwater. Allows water to bead on top of the substrate. For exterior use. Product ready to use, do not dilute. Cleaning with white spirit D-16 (Code 50.012).</p>	<p>Recommended for improving protection against rain on vertical surfaces. Maintains breathability on non-vitrified brick, sandstone, natural stone, concrete and masonry, etc. Forms a long-lasting water-repellent barrier that protects the surface from the elements and won't crack or peel with time. Does not alter the appearance of the treated surface.</p>
		20 l 4 l 750 ml
<input checked="" type="checkbox"/> Clear (68.104)		



WATERPROOFING

- _ Horizontal waterproofing
- _ Façades & vertical waterproofing

Horizontal waterproofing

<p>New</p> <p>GOTEPUR ANTI-LEAK <i>Semi-matt</i></p> 	<p>Elastic membrane 100% water-based polyurethane. Anti-leak waterproofing.</p> <p>Formulated with 100% polyurethane resins, providing excellent waterproofing and mechanical properties. Provides high resistance to UV rays and strong adhesion to mineral surfaces. Maximum elasticity against cracks ranging from 2 to 4mm. Effective anti-carbonation barrier. Improves surface energy efficiency levels.</p> <p>Designed for exterior use. Cleaning and dilution with water.</p>	<p>Recommended for waterproofing roofs and terraces exposed to continuous traffic. It is also particularly suitable for addressing moisture issues and situations where maximum resistance to static water is required.</p> <p><i>APPROVAL CERTIFICATES: Direct pull-off adhesion - Permeability to rain water and water vapour - Crack-resistance Class A5 - Solar reflective</i></p> <p style="text-align: right;">15 l</p>
<p>New</p> <p>JUNOTERAS PUR ANTI-LEAK <i>Semi-matt</i></p> 	<p>Elastic waterproof and anti-leak paint with polyurethane.</p> <p>Formulated with acrylic and polyurethane copolymers, with excellent waterproofing and mechanical properties. Perfect adhesion to mineral surfaces. Good resistance to UV rays. High filling capacity for cracks and small fissures up to 0.6 mm.</p> <p>Improves surface energy efficiency levels. Designed for exterior use. Cleaning and dilution with water.</p>	<p>Recommended for waterproofing roofs and terraces without cracks or with microcracks, provided there is a water run-off slope greater than 1%. It is also particularly suitable for addressing moisture issues in hard-to-reach areas not exposed to continuous traffic and where minimal water absorption is required.</p> <p style="text-align: right;">15 l 4 l</p>
<p>JUNOTERAS <i>Semi-matt</i></p>  <p>Waterproofing Colour CARD</p>	<p>Elastomeric waterproofing paint.</p> <p>Formulated with acrylic-styrene copolymers. Junoteras provides excellent surface adhesion and opacity. Improves surface energy efficiency.</p> <p>For exterior use. Cleaning and dilution with water.</p>	<p>Recommended for vertical and horizontal waterproofing on façades, terraces and roofing without cracks or with micro-cracks, provided there is a run-off slope of over 1%. Also particularly suitable for eliminating moisture problems in hard to reach places that are not exposed to continuous traffic, and for painting and renewing tired looking roof tiles.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Transmission of liquid water and water vapour - Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l 4 l</p>

Façades & vertical waterproofing

ELASTIFLEX PLUS

Semi-matt



Water-based elastomeric paint with maximum elasticity and extraordinary crack resistance (certified to withstand cracks up to 2 mm while able to bridge cracks up to 4 mm). With anti-mould protection.

Formulated with photocrosslinkable acrylic resins with anti-carbonation protection and excellent mechanical and waterproofing properties. Wide range of permanent elasticity (from -30°C to 60°C). Improves surface energy efficiency.

For exterior use.

Cleaning and dilution with water.



Recommended for vertical waterproofing on façades, terraces and roofing without cracks or with cracks up to 4 mm, provided there is a run-off slope above 1%. Also particularly suitable for eliminating moisture problems in hard to reach places that are not exposed to continuous traffic.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Transmission of liquid water and water vapour - Class A5 crack resistance - Fire retardant to B-s1,d0 standard.

ADHESION	PERMEABILITY	ANTI-CARBONATION
TRANSMISSION	RESISTANCE	SOLAR REFLECTIVE
		FIRE RETARDANT B-s1,d0

15 l

White (62.767)

ELASTIFLEX

Semi-matt



Water-based elastomeric paint with maximum elasticity and extraordinary crack resistance (certified to withstand cracks up to 0,9 mm while able to bridge cracks up to 1,5 mm). With anti-mould protection.

Formulated with photocrosslinkable acrylic resins with anti-carbonation protection and excellent mechanical and waterproofing properties. Wide range of permanent elasticity (from -30°C to 60°C). Improves surface energy efficiency.

For exterior use.



Recommended for vertical waterproofing on façades, terraces and roofing without cracks or with micro-cracks up to 1,5 mm, provided there is a run-off slope above 1%. Also particularly suitable for eliminating moisture problems in hard to reach places that are not exposed to continuous traffic.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Transmission of liquid water and water vapour - Class A4 crack resistance - Fire retardant to B-s1,d0 standard.

ADHESION	PERMEABILITY	ANTI-CARBONATION
TRANSMISSION	RESISTANCE	SOLAR REFLECTIVE
		FIRE RETARDANT B-s1,d0

15 l

4 l

White base/P (62.601)

Red* (62.602)

Deep base/TR (62.695)

JUNO Façades Colour CARD





























Waterproofing Colour CARD


















INTERIOR

- _ Interior emulsions
- _ Trade emulsions ideal for spraying
- _ Specialist interior paints
- _ AENOR certified washable paints
- _ Interior tinting bases
- _ Sealers
- _ Stainblocks




Interior emulsions

<p>B-12 Semi-matt</p>  	<p>Premium water-based lustre paint with excellent levelling, washability and a silky touch. With anti-mould protection.</p> <p>Premium vinyl copolymer-based paint with broad spectrum of anti-fungal and mould protection. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p><input type="checkbox"/> White (72.010)</p>	<p>Recommended for decorating plaster, cement or masonry surfaces that require mould protection. Specified and used in high-end decoration jobs for maximum finish and protection. Also recommended for kitchens and bathrooms, or for high-traffic areas such as hallways. Highly wet-rub resistant.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p>  <p>15 l 4 l 750 ml</p>
<p>B-10 Semi-matt</p>  	<p>Durable water-based paint with a semi-matt lustre finish. With anti-mould protection and non-drip/splatter formulation.</p> <p>B-10 is a high quality vinyl copolymer paint offering excellent coverage, opacity and ease of application. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p><input type="checkbox"/> White (72.000)</p>	<p>Ideal for high-quality interior decoration of walls and ceilings in any type of building. Washable and stain resistant, perfect for kitchens, children's rooms, hallways, etc.</p> <p>B-10 splashes to a minimum level when applied making it ideal for decorating lived-in spaces.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p>  <p>15 l 4 l 750 ml</p>
<p>B-7 ECOLOGICAL Matt</p>  	<p>Odourless eco-certified interior emulsion.</p> <p>High quality certified ecological emulsion paint. Formulated with vinyl copolymers, free from solvents, volatile organic compounds (VOCs) and alkyl phenol oxyethylene derivatives.</p> <p>B-7 is odourless and free from harmful substances. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p><input type="checkbox"/> White (72.195)</p>	<p>Ideal for decorating walls and ceilings where a quality matt silky smooth finish is required. Recommended for decorating hospitals, nurseries, baby rooms or spaces for hypersensitive people, thanks to its zero emissions of volatile organic components. Permits immediate use of spaces after application. B-7 is highly wet-rub resistant.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - TÜV mark pollutant tested - Eco-label (European Eco-label) - Fire retardant to B-s1,d0 standard - Certified Class 2 for Washability and Opacity as per standard UNE-EN 13300-2002.</p>       <p>15 l 4 l</p>
<p>B-5 Matt</p>  	<p>Versatile quality interior matt emulsion. Water-based paint with great hiding power and coverage. With anti-mould protection and non-drip/splatter formulation.</p> <p>Formulated with acrylic copolymers with anti-fungicidal and anti-mould agents. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p><input type="checkbox"/> White (73.001)</p>	<p>B-5 dries to a beautiful, smooth matt finish that is fully wipeable and formulated to help conceal surface imperfections. Also ideal for protection against the formation of fungi and mould in kitchens and bathrooms. B-5 is also fire retardant. Wet-rub resistant.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified Class 2 for Washability and Class 1 for Opacity as per standard UNE-EN 13300-2002.</p>    <p>15 l 10 l 4 l 2,5 l 750 ml</p>
<p>B-4 NATURE Matt</p>  	<p>Odourless water-based eco-paint with A⁺ certification for maximum indoor air quality.</p> <p>Formulated with vinyl copolymers. Catalogued with A⁺ certification, the maximum classification for indoor air quality, guaranteeing the lowest possible emission levels.</p> <p>B-4 is an ecological, solvent-free, odourless white emulsion offering a smooth matt finish that is fully wipeable and formulated to help conceal surface imperfections. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p><input type="checkbox"/> White (73.271)</p>	<p>Recommended for decorating hospitals, nurseries, baby rooms or indoor spaces for hypersensitive people. Allows immediate use of painted spaces.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - A⁺ Certification for low emissions and maximum indoor quality - Fire retardant to B-s1,d0 standard.</p>   <p>15 l 4 l</p>




Trade emulsions ideal for spraying




<p>J-33 Extra-Matt</p>  	<p>High opacity and coverage extra-matt emulsion paint. With anti-mould protection and non-splatter technology.</p> <p>Formulated with acrylic copolymers. For interior and exterior use. Cleaning and dilution with water.</p>	<p>Recommended for general use in construction and decoration, especially for walls and ceilings where an extra-matt finish is required.</p> <p><i>APPROVAL CERTIFICATES: Fire retardant to B-s1,d0 standard (white only) - Certified Class 1 for Washability and Opacity as per standard UNE-EN 13300-2002.</i></p> <div style="text-align: right;">    </div> <p style="text-align: right;">15 l 4 l</p> <p><input type="checkbox"/> White (73.424)</p>
<p>J-28 Extra-matt</p> 	<p>Water-based emulsion paint with an extra-matt finish, special for coating projected plaster and plasterboards. With anti-mould protection.</p> <p>Formulated with acrylic copolymers in aqueous dispersion, titanium dioxide and extenders. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p> 	<p>Recommended for general use in construction and decoration, especially to hide fillers and joints on applied plaster, plasterboard or gypsum. J-28 is excellent for spraying large surface areas and touches up very well. Resistant to wet rubbing and scuffing.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified Class 2 for Washability and Opacity as per standard UNE-EN 13300-2002.</i></p> <div style="text-align: right;">    </div> <p style="text-align: right;">15 l 4 l</p> <p><input type="checkbox"/> White (73.168)</p>
<p>J-25 Matt</p> 	<p>High opacity interior emulsion paint with superb coverage and anti-mould protection.</p> <p>Formulated with acrylic copolymers in aqueous dispersion, titanium dioxide and extenders. Excellent bright opaque white finish at excellent value for money. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p>i</p>	<p>Recommended for general use in construction and decoration, especially for walls and ceilings where a matt finish is required. Resistant to wet rubbing and scuffing. J-25 is excellent for spraying and touches up very well.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard (white only) - Certified Class 2 for Washability and Class 1 for Opacity as per standard UNE-EN 13300-2002.</i></p> <div style="text-align: right;">    </div> <p style="text-align: right;">15 l 4 l</p> <p><input type="checkbox"/> White (73.150)</p> <p><input checked="" type="checkbox"/> Black* (73.173)</p>

Specialist interior paints










<p>ANTI-CONDENSATION Matt</p> 	<p>Water-based special anti-condensation paint. With anti-mould protection.</p> <p>Formulated with acrylic copolymers and glass beads which prevent water condensation and mould growth on its surface. For interior use. Ready to use. Do not dilute.</p> 	<p>Specifically designed to significantly reduce condensation on walls and ceilings in humid environments - by preventing condensation mould will not grow. Ideal for use in bathrooms, kitchens, pantries, north facing rooms with poor insulation, roller shutter boxes, fitted wardrobes, computer rooms, etc. Also ideal for painting cold-water pipes.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Conductivity certificate.</i></p> <div style="text-align: right;">  </div> <p style="text-align: right;">15 l 4 l 750 ml</p> <p><input type="checkbox"/> White (62.650)</p>
--	---	--

AENOR certified washable paints




<p>N-5 Matt</p> 	<p>Matt water-based emulsion paint with AENOR certification for washability. With anti-mould protection.</p> <p>Based on acrylic copolymers in aqueous dispersion. Resistant to wet rubbing, breathable, with excellent hiding power and maximum performance. For interior use. Cleaning and dilution with water.</p> 	<p>Recommended for general use in construction and decoration on typical surfaces such as plaster, plasterboard, gypsum, concrete, cement, etc. Ideal for spraying. Recommended for public and private projects where finishes with guaranteed washability and anti-mould protection is required. Ideal for high traffic and frequently used public areas, such as schools, hospitals, kindergardens, prisons, etc.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - AENOR Certified for washability - Fire retardant to B-s1,d0 standard.</i></p> 
		15 l 4 l 750 ml
	<input type="checkbox"/> White (73.040)	

<p>CASTOR-N Matt</p> 	<p>Matt water-based emulsion paint with AENOR certification for washability. With anti-mould protection.</p> <p>Based on acrylic copolymers in aqueous dispersion. For interior use. Cleaning and dilution with water.</p> 	<p>Recommended for general use in construction and decorating on plaster, plasterboard, concrete, cement surfaces, etc. Ideal for spraying.</p> <p>Great washability, with high hiding power and great performance. Required in public and private projects with a comprehensive system of certified building specifications.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - AENOR - Fire retardant to B-s1,d0 standard.</i></p> 
		15 l 4 l
	<input type="checkbox"/> White (73.113)	





Interior tinting bases

<p>JUNOPROF Matt</p>    <p>JUNOMATIC Tinting System</p>	<p>High performance interior emulsion for tinting system with excellent washability and class leading coverage and opacity. With anti-mould protection and non-drip/splatter formulation.</p> <p>Formulated with acrylic copolymers in aqueous dispersion. For interior use. Cleaning and dilution with water.</p> 	<p>Low odour emulsion giving a tough finish on surfaces of blockwork/brickwork, cement render, concrete, plaster, plasterboards, gypsum, wallboards, etc. Ideal for designer home decoration, hotels, hospitals, public buildings, etc.</p> <p>Available in a market leading number of colours incl. 300 exclusive new JUNO Designer Palette colours.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - A+ Certified - Fire retardant to B-s1,d0 standard - Meets health related evaluation procedure for emissions of volatile organic compounds AgBB as per German evaluation standards - Certified Class 1 for Washability and Class 2 for Opacity as per UNE-EN 13300:2002.</i></p> 
		<div style="background-color: red; color: white; padding: 2px; display: inline-block;">New</div> 12 l 4 l 2,5 l 750 ml
	<input type="checkbox"/> White base/P (88.750)	
	 Medium base/D (88.751)	
	 Deep base/TR (88.752)	
	 Yellow base/GL* (88.753)  Red base/RD* (88.754)	

Sealers

<p>HIDROCRIL Semi-matt</p> 	<p>Concentrate water-based acrylic sealer with excellent penetration and adhesion. For interior and exterior use. Cleaning and dilution with water. Mixing ratio 4:1 (Water / Hidrocril).</p>	<p>Hidrocril evens out surface absorption. Recommended as a sealer for surfaces that have problems with adhesion (pearlite, concrete, plaster, cement, asbestos cement, brick), or require binding (tempera, lime, whitewash or unconsolidated paints).</p> <p style="text-align: right;">20 l 4 l 750 ml</p>
<p><input checked="" type="checkbox"/> Clear (81.006)</p>		
<p>AQUASELL Matt</p> 	<p>Special water-based sealer for projected plasters. Formulated with acrylic resins in aqueous dispersion with great filling and sealing capacity. For interior and exterior use. Cleaning and dilution with water.</p>	<p>Recommended as a base coat on surfaces on which there are significant differences in absorption levels (mineral substrates, drywalls or applied/projected plasters).</p> <p><i>APPROVAL CERTIFICATES: Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l 4 l</p>
<p><input type="checkbox"/> White (21.203)</p>		
<p>ANTI-HUMIDITY SEALER Matt</p> 	<p>Quick-drying anti-humidity sealer. Formula based on pliolite resins with portland cement and additives with insulating properties. Ideal for both interior and exterior walls subjected to occasional humidity, grease or oily conditions, preventing their appearance. Cleaning and dilution with white spirit D-16 (Code 50.012).</p>	<p>Recommended to eliminate problems of occasional humidity in ceilings, walls, basements, garages, etc. Its quick drying allows repainting with all types of paints, wallpapering or applying any other suitable surface treatment.</p> <p style="text-align: right;">4 l 750 ml</p>
<p><input type="checkbox"/> White (88.000)</p>		

Stain blocks

<p>STAIN BLOCK Matt</p> 	<p>Synthetic stain block with Plioway. Odourless. Formulated with high quality Plioway resins with stain-resistant and mould prevention properties. Suitable for use on interior walls and ceilings. Cleaning and dilution with odourless solvent D-69 (Code 50.073).</p>	<p>Recommended for all types of surfaces that have damp, grease, nicotine or other stains, or surfaces that have lost their hue. Also recommended as a finishing coat. When re-coating with water-based emulsions ensure the stain block has fully cured to avoid stains resurfacing.</p> <p style="text-align: right;">15 l 4 l 750 ml</p>
<p><input type="checkbox"/> White (21.350)</p>		
<p>JUNOSTOP Matt</p> 	<p>Synthetic stain block with Plioway. Formulated with special resins with stain resistant and mould prevention properties. Suitable for use on interior walls and ceilings. Cleaning and dilution with odourless solvent D-69 (Code 50.073).</p>	<p>Recommended for all types of surfaces that have damp, grease, nicotine or other stains, or surfaces that have lost their hue. Also recommended as a finishing coat. When re-coating with water-based emulsions ensure the stain block has fully cured to avoid stains resurfacing.</p> <p style="text-align: right;">15 l 4 l 750 ml</p>
<p><input type="checkbox"/> White (21.300)</p>		
<p>STAIN BLOCK SPRAY Matt</p> 	<p>White synthetic stain blocking spray. Quick drying and easy application stain blocker. For interior and exterior use. 500 ml aerosol.</p>	<p>Recommended for covering and preventing the reappearance of all types of stubborn stains (grease, damp, nicotine, felt tip pens, etc.). Thanks to its easy application, repainting, quick-drying properties and great durability, it can be used as a base for other topcoats.</p> <p style="text-align: right;">500 ml</p>
<p><input type="checkbox"/> White (760.135)</p>		
<p>AQUATAPA Matt</p> 	<p>Odourless water-based stain block primer. Formulated with acrylic resins with stain resistant properties to seal, bind and prevent the migration of stains through the paint film. For interior walls and ceilings. Cleaning with water. Do not dilute.</p>	<p>Recommended for stains including smoke damage, nicotine/inks and ideal for areas exposed to smoke, steam or condensation (boilers outlets, tanks, fireplaces). Seals mineral substrates such as powdery surfaces, limewash and distemper. Also recommended as a finishing coat.</p> <p><i>APPROVAL CERTIFICATES: Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l 4 l 750 ml</p>
<p><input type="checkbox"/> White (21.205)</p>		



FLOOR COATINGS

- _ 1K Floor coatings
- _ 2K Floor coatings
- _ 100% Solids 2K Epoxy system
- _ Pool/Milking parlour/Traffic Marking
- _ Line marking for grass/turf

1K Floor coatings

JUNOSOL Semi-matt



Easy to apply and quick-dry water-based one component floor paint.

Formulated with styrene-acrylic resins that provide great strength.

For interior and exterior use.

Cleaning and dilution with water.

Suitable for internal and external applications such as on tarmac, concrete, asphalt, walls and bricks. Ideal for painting sports facilities, line marking and car parks with light traffic.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistance with special micro-beads (see page 36) - Fire retardant to B-s1,d0 standard.



SLIP RESISTANT

FIRE RETARDANT
B-s1,d0



15 l

4 l

White (06.162)

Tennis green* (06.150)

Cement grey* (06.163)

Turkish red* (06.160)

Light grey* (06.164)

NA

Yellow* (06.166)

NA

FLOOR COATINGS
COLOUR CARD

DYNAMOL Satin



Quick-drying chlorinated rubber paint with high resistance to acids.

Formulated with chlorinated rubber resins with high resistance to acids and alkalis.

For interior and exterior use.

Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).

Ideally suited for application to brickwork, swimming pool enclosures, pool structures, walls, floors, parkings, sewage tanks, etc. Also suitable for milking parlours, stables, kennels and catteries. Not suitable for painting tar and/or bituminous asphalt surfaces due to bleeding.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistance with special micro-beads (see page 36).



SLIP RESISTANT



15 l

4 l

750 ml

White (09.500)

Tennis red* (09.568)

Gris perla* (09.533)

Yellow* (09.525)

Tennis green* (09.552)

FLOOR COATINGS
COLOUR CARD

2K Floor coatings - Water-based

DYNAPOK AGUA FLOOR PRIMER / CLEAR TOPCOAT 2/C Satin



Two-pack water-based floor epoxy primer.

Formulated with epoxy resin in aqueous solution. Excellent substrate penetration and filling capacity.

Also formulated to be used as a clear topcoat.

For interior use.

Cleaning and dilution with water.

As primer (dilute 30%) for sealing new or consolidated concrete or cement surfaces. As finishing coat (dilute 10%) for the protection of concrete surfaces exposed to contact with water, grease, acids or diluted alkalis.

Ideal for use in industrial applications in general, and especially in the food and health sector industries as it is water based and no solvent is required.

15 l

4 l

Clear (07.160)

DYNAPOK AGUA EPOXY Satin



Certified hygiene epoxy coating. Ideal for spaces with reduced access to ventilation.

A two-pack epoxy coating formulated with non-toxic epoxy resin in a water-based solution. High chemical resistance and great strength.

Interior use.

Cleaning and dilution with water.

Ideal where hygiene coating is specified, and essential for interior spaces with reduced access to ventilation, where conventional paints with organic solvents would be toxic.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOC's (German AgBB 2018) - A+ Certified for clean interior environment - Non-toxicity cert.: Non migration of certain elements EN 71-3:2013+A2:2017 - Class 3 anti-slip resistant with special micro-beads (see page 36) - Fire retardant rating for floors to Bfl-s1 standard.



AgBB

A+

CERTIFICATE
HEALTH

SLIP RESISTANT

FIRE RETARDANT
Bfl-s1



15 l

4 l

White base/P (07.132)

Grey* (07.145)

Deep base/TR (07.133)

FLOOR COATINGS
COLOUR CARD

JUNOMATIC Tinting System

New

AQUAPUR FLOOR COATING
High Satin

JUNOMATIC Tinting System

Two-component water-based polyurethane coating with low VOC emissions. Especially designed for interiors, garage floors, parking lots, etc.

Formulated with water-based polyurethane resins creating a hard and chemically resistant film withstanding wear and tear. Suitable for both interior and exterior use. Cleaning and dilution with water.

Recommended as a coating for concrete surfaces in the general industry or on concrete where it is not possible to completely eliminate moisture from the substrate. Also recommended in enclosed, unventilated spaces and on asphalt products such as tar, bituminous materials, and slurries. Particularly recommended as a sealing and protective coat on 100% solid epoxy flooring systems.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - A+ Certified for clean interior environment - Meets health related evaluation procedure for emissions of VOC's (German AgBB 2018) - Fire retardant to B-s1,d0 standard.



4 l

White base/P (8.340)

Deep base/TR (8.341)

Two-pack floor paints - Solvent-based

PRIMER IMPRIMAX
Semi-gloss

Two-pack synthetic floor epoxy primer.

Silane-modified epoxy-polyamide reinforcing primer providing class-leading adhesion on smooth non-porous surfaces, like power-floated concrete and tiles.

For interior use.

Cleaning and dilution with epoxy solvent D-90 (Code 50.010).

Recommended as an epoxy adhesion primer coating on non-porous surfaces for interior epoxy systems.

15 l 4 l 1 l

Clear (48.725)

PAVIMYC
Gloss

COLOUR CARD

Two-pack epoxy floor paint with excellent hardness and adhesion properties.

Ensures effective protection against carbonation of concrete. Resistance to acids, alkalis and solvents, and provides erosion protection to concrete pavements exposed to traffic, chemicals, cleaning systems, etc.

For interior use only.

Cleaning and dilution with epoxy solvent D-90 (Code 50.010).

Product widely used on concrete floors in industrial and non-industrial settings. Ideal for indoor car parks, laboratories, chemical and pharmaceutical facilities, mechanical workshops, etc. Not recommended for use on asphalt, tar or bitumen treated surfaces.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistant with added special micro-beads (see page 36).



15 l 4 l












Clear (07.815)

English red* (07.812)



Green* (07.814)

Grey* (07.807)


100% Solids 2K Epoxy system

<p>PAVIMYC HB EPOXY PRIMER <i>High Satin</i></p> 	<p>2K Epoxy Primer 100% solids. Formulated based on modified epoxy resins. Easy application. Impermeable to water and water vapour. Very good adhesion and penetration. Interior use and application. Use D-90 thinner for cleaning. (Code 50.010).</p> <p><input type="checkbox"/> Clear (07.915)</p>	<p>Recommended for cement and concrete substrates. Creates solid floor paint system in combination with Pavimyc HB 2/C (07.931) Primer coat for JUNO's PAVIMYC HB Floor systems (smooth, non -slip, multi-layer or self -leveling floor systems).</p> <p style="text-align: right;">20 kg</p>									
<p>PAVIMYC HB <i>Gloss</i></p>  <p>JUNOMATIC Tinting System</p>	<p>High-build (100% Solids) pigmented 2K epoxy coating to seal and protect floors. Formulated with 100% solids epoxy resins and pigments achieving high chemical resistance and hardness. Great opacity and coverage level. Allows for an even floor surface with low paint consumption. Facilitates cleaning of any type of surface stains/dirt. For interior use. Use D-90 thinner for cleaning. (Code 50.010).</p> <p><input type="checkbox"/> Deep base/TR (07.931)</p>	<p>Recommended to protect concrete floors from wear and tear, chemical agents thus expanding their life cycle. Pavimyc HB offers different systems for continuous coatings. (smooth, non-slip, self-levelling, multi-layer) with one and same product. Indicated for garages, workshops, parkings, wineries, warehouses, industrial factories, data centres, etc. Not recommended for use on asphalt, tar or bitumen treated surfaces.</p> <p><i>APPROVAL CERTIFICATES: CE Certified (see below) - Bfl-s1 Euroclass Fire retardant certified - Class 3 Anti-slip rating when used with Pavimyc HB Microbeads (see page 36).</i></p> <table border="0"> <tr> <td>UNE-EN 1062-6:2003</td> <td>UNE-EN 1062-3:2008</td> <td rowspan="4">    </td> </tr> <tr> <td>UNE-EN 13529:2005</td> <td>UNE-EN ISO 6272-1:2012</td> </tr> <tr> <td>UNE-EN ISO 7783:2019</td> <td>UNE-EN 1542:2000</td> </tr> <tr> <td>UNE-EN ISO 5470-1:2017</td> <td>UNE-EN 13892-2:2003</td> </tr> </table> <p style="text-align: right;">20 kg</p>	UNE-EN 1062-6:2003	UNE-EN 1062-3:2008	  	UNE-EN 13529:2005	UNE-EN ISO 6272-1:2012	UNE-EN ISO 7783:2019	UNE-EN 1542:2000	UNE-EN ISO 5470-1:2017	UNE-EN 13892-2:2003
UNE-EN 1062-6:2003	UNE-EN 1062-3:2008	  									
UNE-EN 13529:2005	UNE-EN ISO 6272-1:2012										
UNE-EN ISO 7783:2019	UNE-EN 1542:2000										
UNE-EN ISO 5470-1:2017	UNE-EN 13892-2:2003										

Pool/Milking parlour/Traffic Marking

<p>JUNOSPORT <i>Satin</i></p> 	<p>Water-based durable, strong and highly flexible paint for swimming pools. Formulated with pure acrylic resins to resist the destructive effects of swimming pool chemicals. Exclusive use for concrete type swimming pools. For interior and exterior use. Cleaning and dilution with water.</p> <p><input type="checkbox"/> Blue* (06.105)</p>	<p>Formulated for use over old or new concrete based swimming pools. Applied by brush, roller or spray, displaying excellent adhesion over sound previously painted surfaces. Also recommended as floor coating for other types of sports facilities and car parks with light traffic. Blue colour is correct for marking disability car parking spaces.</p> <p style="text-align: right;">4 l</p>
<p>PISCICLOR <i>Satin</i></p> 	<p>Solvent-based durable, strong and highly flexible paint for swimming pools/milking parlours. Formulated with chlorinated rubber resins with extraordinary resistance to weathering, chemical damage and discolouration. Exclusive use for concrete type swimming pools. For interior and exterior use. Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).</p> <p><input type="checkbox"/> Blue* (09.180)</p>	<p>Recommended for painting swimming pools and milking parlours, sports facilities and car parks with light traffic. Also recommended as floor coating for other types of sports facilities and car parks with light traffic. Blue colour is correct for marking disability car parking spaces.</p> <p style="text-align: right;">4 l</p>

Line marking for grass/turf

<p>JUNOLINEA <i>Matt</i></p> 	<p>Water-based line marking paint with high hiding power. Not harmful to natural grass. Formulation based on high quality acrylic copolymers, giving bright white lines. For interior and exterior use.</p> <p><input type="checkbox"/> White (62.550)</p>	<p>Junolinea is the ultimate white line marking paint for use on football, rugby, hockey pitches and tennis courts and cricket squares. It is used by top professional clubs and give long lasting brilliant white lines (also used on farms, construction sites, hills/woodland, paths for occasional marking/signposting).</p> <p style="text-align: right;">10 l</p>
---	---	--



TRIM PAINT

- _ Solvent-based enamels
- _ Water-based enamels
- _ Tinting bases - Decorative
- _ Tinting bases - Industrial
- _ Adhesion & anti-corrosive primers
- _ Wood primers

Solvent-based enamels

JUNOLAC ANTIOXIDANT

Gloss



Satin



JUNOLAC ANTI-OX
Colour CARD
JUNOMATIC Tinting System

Quick-drying-antioxidant synthetic self-priming enamel.

Ready to apply directly on new or old steel or iron, whether bare or pre-painted. High gloss enamel, with excellent resistance to weathering and corrosive environments. For large surface areas the use of retarding thinner D-75 (Code 50.107) is recommended.

For interior and exterior use.

Cleaning and dilution with D-16 thinner (Code 50.012).



Recommended for iron or steel surfaces where exhaustive preparation of the substrate is not possible (large structures, gates, railings, bridges, etc.).
Touch dry and repaintable in 1 hour.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Anti-corrosive properties certified according to UNE 48316: 2014.

Gloss finish		4 l	750 ml	375 ml
<input type="checkbox"/> White (04.860)	<input type="checkbox"/> Red* (04.866)			
<input type="checkbox"/> Black* (04.861)	<input type="checkbox"/> Golden yellow* (04.867)			
<input type="checkbox"/> Ochre* (04.862)	<input type="checkbox"/> Medium grey* (04.868)			
<input type="checkbox"/> Arabia Brown* (04.863)	<input type="checkbox"/> Marine blue* (04.869)			
<input type="checkbox"/> Txoko brown* (04.864)	<input type="checkbox"/> Spring green* (04.870)			
<input type="checkbox"/> Bordeaux red* (04.865)	<input type="checkbox"/> Pine green* (04.871)			
<input type="checkbox"/> White base/P (04.897)	New			NA
<input type="checkbox"/> Deep base/TR (04.895)				NA

In white and black

Satin finish		4 l	750 ml	375 ml
<input type="checkbox"/> White (04.880)	<input type="checkbox"/> Red* (04.886)			
<input type="checkbox"/> Black* (04.881)	<input type="checkbox"/> Golden yellow* (04.887)			
<input type="checkbox"/> Ochre* (04.882)	<input type="checkbox"/> Medium grey* (04.888)			
<input type="checkbox"/> Arabia Brown* (04.883)	<input type="checkbox"/> Marine blue* (04.889)			
<input type="checkbox"/> Txoko brown* (04.884)	<input type="checkbox"/> Spring green* (04.890)			
<input type="checkbox"/> Bordeaux red* (04.885)	<input type="checkbox"/> Pine green* (04.891)			
<input type="checkbox"/> White base/P (04.894)	New			NA
<input type="checkbox"/> Deep base/TR (04.893)				NA

In white and black

JUNOLAC

Gloss



Satin / Matt



High-solid synthetic enamel paint with great durability.

Premium quality high-solid solvent-based alkyd formulation which offers excellent flow, giving surfaces a tough, durable high-gloss finish.

For use on interior and exterior surfaces (gloss and satin finishes).

Cleaning and dilution with D-16 thinner (Code 50.012).



Recommended for interior and exterior use on wood and metal surfaces such as doors, window trims, furniture, etc.

Applied in thin layers to promote proper drying conditions and curing.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ certificate - Fire retardant to B-s1,d0 standard.

Gloss finish		4 l	750 ml	375 ml
<input type="checkbox"/> White (15.000)	<input type="checkbox"/> Black* (15.001)			
Satin finish		4 l	750 ml	375 ml
<input type="checkbox"/> White (15.100)	<input type="checkbox"/> Black* (15.101)			
Matt finish		4 l	750 ml	375 ml
<input type="checkbox"/> White (15.200)	<input type="checkbox"/> Black* (15.201)			NA

JUNOPLUS


Gloss



Satin



Matt



Synthetic alkyd-based enamel with wide range of colours.

Formulated with alkyd resins.

For use on interior and exterior surfaces (matt finish for interior use only).

Cleaning and dilution with D-16 thinner (Code 50.012).



Recommended for primed wood and metal surfaces. Can also be used on furniture.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.



! Gloss finish

4 l

750 ml

375 ml

White (16.000)	Carriage green* (16.011)
Black* (16.001)	Fire red* / RAL 2002 (16.012)
Chamois* (16.002)	Wagon red* / RAL 3005 (16.021)
Meadow* (16.003)	Blood red* / RAL 3000 (16.022)
Grass green* (16.004)	Medium yellow* / RAL 1028 (16.029)
Ivory* (16.005)	Light grey* / RAL 7035 (16.031)
Traffic grey* (16.006)	Cloud grey* / RAL 7001 (16.038)
Ochre* (16.007)	Dark grey* / RAL 7031 (16.039)
Blue* / RAL 5012 (16.008)	Meadow green* / RAL 6001 (16.054)
Ultramarine / RAL 5002 (16.009)	Moss green* / RAL 6005 (16.058)
Bright blue* / RAL 5017 (16.010)	Arabia Brown* (16.069)

Colours on demand (RAL colour chart, available from the Junomatic system, parting from colours in the Junoplus chart as bases)

! Satin finish

4 l

750 ml

375 ml

White (16.100)	Black* (16.101)
Ultramarine* / RAL 5002 (16.109)	Light grey* / RAL 7035 (16.131)
Wagon red* / RAL 3005 (16.121)	Meadow green* / RAL 6001 (16.154)
Blood red* / RAL 3000 (16.122)	Moss green* / RAL 6005 (16.158)
Medium yellow* / RAL 1028 (16.129)	Arabia Brown* (16.169)

Colours on demand (RAL colour chart, available from the Junomatic system, parting from colours in the Junoplus chart as bases)

! Matt finish (for interior use only)

4 l

750 ml

375 ml

White (16.200)	Black* (16.201)	NA
----------------	-----------------	-----------

OXIFORJA

Forja



Synthetic enamel with a unique forged iron metallic finish effect and antioxidant properties.

Formulated with alkyd resins and additives with a high resistance to weathering.

For interior and exterior use.

Cleaning and dilution with white spirit D-16 (Code 50.012).



Recommended for the protection and decoration of lamp posts, mail boxes, manhole covers, iron gates, metal structures, fences, urban furniture, etc.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).

!

4 l

750 ml

Black* (05.700)	Base / Steel grey* (05.701)	
Azure (05.720)	Gold (05.722)	Intense black (05.725)
Bronze green (05.721)	Oxide red (05.723)	

Water-based enamels

WATERPLUS Satin / Matt



Single-pack water-based Polyurethane enamel paint. Impeccable lacquered finish for walls, furniture and trims.

Water-based multi-surface polyurethane enamel with excellent hardness washability and chemical resistance. Offers excellent application/levelling properties and opacity for an impeccable finish. Resists rubbing, scratches, impacts and most cleaning products.

For interior use.

Cleaning and thinning with water.

Recommended for all types of surfaces, especially wood and metal carpentry. Ideal for painting furniture, kitchens, doors, window trims, skirting boards, etc. and for perfect smooth and resistant finishes on walls, sandwich panels etc.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified.



New



Finish	15 l	4 l	750 ml
Satin finish			
<input type="checkbox"/> White base/P (10.635)			
<input checked="" type="checkbox"/> Deep base/TR (10.637)	NA		
Matt finish			
<input type="checkbox"/> White base/P (10.640)			
<input checked="" type="checkbox"/> Deep base/TR (10.642)	NA		

JUNOMATIC Tinting System

AQUALAC Gloss / Satin / Matt



Water-based multi-surface enamel, with low odour and easy-application properties.

Formulated with quick drying pure acrylic weather resistant resins. Low-odour and extraordinary weather resistance.

For interior and exterior use (gloss and satin finishes). Cleaning and dilution with water.

Recommended for the protection and decoration of properly prepared and primed metal, wood, masonry, plaster/drywall, trims, etc.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified - Fire retardant to B-s1,d0 standard.



Finish	4 l	750 ml
Gloss finish		
<input type="checkbox"/> White base/P (10.300)		
<input checked="" type="checkbox"/> Medium base/D (10.302)		
<input checked="" type="checkbox"/> Deep base/TR (10.303)		
<input checked="" type="checkbox"/> Yellow base/GL* (10.304)		
<input checked="" type="checkbox"/> Red base/RD* (10.305)		
Satin finish		
<input type="checkbox"/> White base/P (10.400)		
<input checked="" type="checkbox"/> Medium base/D (10.402)		
<input checked="" type="checkbox"/> Deep base/TR (10.403)		
<input checked="" type="checkbox"/> Yellow base/GL* (10.404)		
<input checked="" type="checkbox"/> Red base/RD* (10.405)		
Matt finish (for interior use only)		
<input type="checkbox"/> White base/P (10.500)		
<input checked="" type="checkbox"/> Medium base/D (10.502)		
<input checked="" type="checkbox"/> Deep base/TR (10.503)		

AQUALAC Colour CARD

JUNOMATIC Tinting System

New

TILE PAINT Satin

Coming soon

Water-based self-priming enamel for tiles. (No primer required). Ideal for ceramic, stone and glass tiles.

Formulated with resins that provide excellent hardness and high resistance to rubbing, scratches, neutral cleaning products, etc.

Immaculate fine and smooth finish.

Excellent adhesion and opacity.

Outstanding resistance and hardness.

Washable and waterproof.

Low odour.

Quick drying.
















For indoor use.

Recommended for painting tiles in both bathrooms and kitchens due to its excellent hardness and resistance to neutral cleaning products. Withstands repeated water splash and highly humid environments.






















Not recommended for continuous contact with water.

<input type="checkbox"/> White (10.850)			750 ml
---	--	--	--------





Tinting bases - Decorative

JUNOMALTE <i>Gloss / Satin</i>   JUNOMATIC Tinting System	Synthetic enamel for Junomatic tinting system. Wide range of colours. For interior and exterior use (exterior: Gloss finish only). Cleaning and dilution with D-16 white spirit (Code 50.012). 	Especially recommended for primed interior and exterior wood and metal surfaces. APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).											
	<table border="0"> <tr> <td>Gloss finish</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">750 ml</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.990)</td> <td> Medium base/D (88.991)</td> <td> Deep base/TR (88.992)</td> </tr> <tr> <td>Satin finish</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">750 ml</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.993)</td> <td> Medium base/D (88.994)</td> <td> Deep base/TR (88.995)</td> </tr> </table>	Gloss finish	4 l	750 ml	<input type="checkbox"/> White base/P (88.990)	 Medium base/D (88.991)	 Deep base/TR (88.992)	Satin finish	4 l	750 ml	<input type="checkbox"/> White base/P (88.993)	 Medium base/D (88.994)	 Deep base/TR (88.995)
Gloss finish	4 l	750 ml											
<input type="checkbox"/> White base/P (88.990)	 Medium base/D (88.991)	 Deep base/TR (88.992)											
Satin finish	4 l	750 ml											
<input type="checkbox"/> White base/P (88.993)	 Medium base/D (88.994)	 Deep base/TR (88.995)											



Tinting bases - Industrial

JUNORAPID S/R <i>Gloss</i>  JUNOMATIC Tinting System	Quick-drying synthetic enamel for Junomatic industrial tinting system. For interior and exterior use. Cleaning and dilution with quick-dry thinner D-17 (Code 50.004). 	Ideal and recommended for refinishing or applying to metal surfaces such as automated installations, structures, OEM coatings to forklifts, trucks, tractors, trailers, etc. that require a quick drying enamel. Application recommended by spraying. APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Certified for JUNO's protective anti-corrosive systems as per ISO 12944. <div style="float: right; border: 1px solid black; padding: 2px;"> FIRE RETARDANT B-s1,d0 </div> <div style="float: right; border: 1px solid black; padding: 2px;"> C3 </div>												
	<table border="0"> <tr> <td>Gloss finish</td> <td style="text-align: right;">15 l</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">750 ml</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.884)</td> <td colspan="3"></td> </tr> <tr> <td> Deep base/TR (88.885)</td> <td colspan="3"></td> </tr> </table>	Gloss finish	15 l	4 l	750 ml	<input type="checkbox"/> White base/P (88.884)				 Deep base/TR (88.885)				
Gloss finish	15 l	4 l	750 ml											
<input type="checkbox"/> White base/P (88.884)														
 Deep base/TR (88.885)														
JUNOPOXI 2/C <i>Gloss</i>  JUNOMATIC Tinting System	2-component epoxy enamel for Junomatic industrial tinting system. High chemical resistance. A high quality tintable epoxy for interior and industrial use. This product provides great coverage and is easy to apply. Anti-dust function. Cleaning and dilution with epoxy solvent D-90 (Code 50.010). 	Recommended for protecting metal, cement or concrete surfaces in industrial or marine environments. APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistance when adding microbeads (see page 34). <div style="float: right; border: 1px solid black; padding: 2px;"> SLIP RESISTANT </div>												
	<table border="0"> <tr> <td>Gloss finish</td> <td style="text-align: right;">15 l</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">1 l</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.882)</td> <td colspan="3"></td> </tr> <tr> <td> Deep base/TR (88.883)</td> <td colspan="3"></td> </tr> </table>	Gloss finish	15 l	4 l	1 l	<input type="checkbox"/> White base/P (88.882)				 Deep base/TR (88.883)				
Gloss finish	15 l	4 l	1 l											
<input type="checkbox"/> White base/P (88.882)														
 Deep base/TR (88.883)														
JUNORETANO 2/C <i>Gloss / Satin / Matt</i>  JUNOMATIC Tinting System	2K multi-surface polyurethane coating for Junomatic industrial tinting system. Great weather resistance. Anti-corrosion certified system. Suitable for interior and exterior use. Cleaning and dilution with Junoretano solvent D-70 (Cód. 50.007). 	Recommended for effective protection of all types of surfaces exposed to aggressive atmospheres (metals, concrete, wood, polyester, PVC, etc.). CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Slip resistance of up to Class 3 by adding microbeads (see page 35) - Fire Retardant B-s1,d0 - Certified for JUNO Anticorrosive Systems with UNE EN ISO 12944. <div style="float: right; border: 1px solid black; padding: 2px;"> SLIP RESISTANT </div> <div style="float: right; border: 1px solid black; padding: 2px;"> FIRE RETARDANT B-s1,d0 </div> <div style="float: right; border: 1px solid black; padding: 2px;"> C4 </div> <div style="float: right; border: 1px solid black; padding: 2px;"> C5 </div>												
	<table border="0"> <tr> <td>Gloss finish</td> <td style="text-align: right;">15 l</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">1 l</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.880)</td> <td colspan="3"></td> </tr> <tr> <td> Deep base/TR (88.881)</td> <td colspan="3"></td> </tr> </table>	Gloss finish	15 l	4 l	1 l	<input type="checkbox"/> White base/P (88.880)				 Deep base/TR (88.881)				
	Gloss finish	15 l	4 l	1 l										
	<input type="checkbox"/> White base/P (88.880)													
 Deep base/TR (88.881)														
<table border="0"> <tr> <td>Satin finish</td> <td style="text-align: right;">15 l</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">1 l</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.872)</td> <td colspan="3"></td> </tr> <tr> <td> Deep base/TR (88.873)</td> <td colspan="3"></td> </tr> </table>	Satin finish	15 l	4 l	1 l	<input type="checkbox"/> White base/P (88.872)				 Deep base/TR (88.873)					
Satin finish	15 l	4 l	1 l											
<input type="checkbox"/> White base/P (88.872)														
 Deep base/TR (88.873)														
<table border="0"> <tr> <td>Matt finish</td> <td style="text-align: right;">4 l</td> <td style="text-align: right;">1 l</td> </tr> <tr> <td><input type="checkbox"/> White base/P (88.801)</td> <td colspan="2"></td> </tr> <tr> <td> Deep base/TR (88.802)</td> <td colspan="2"></td> </tr> </table>	Matt finish	4 l	1 l	<input type="checkbox"/> White base/P (88.801)			 Deep base/TR (88.802)							
Matt finish	4 l	1 l												
<input type="checkbox"/> White base/P (88.801)														
 Deep base/TR (88.802)														

Adhesion & anti-corrosive primers

<p>METALEX Matt</p> 	<p>Anti-corrosive zinc-phosphate primer. Formulated with zinc phosphate and alkyd resins with rust inhibiting properties. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p><input type="checkbox"/> White (27.000)</p>	<p>Recommended for protecting metal surfaces that require protection against corrosion (except galvanized and aluminium surfaces).</p> <p style="text-align: right;">4 l 750 ml</p>
<p>MULTI-SUPPORT Matt</p>  <p>JUNOPLUS Colour CARD</p>	<p>All-purpose synthetic multi-surface adhesion primer. Premium quality quick drying multi-surface primer based on modified alkyd resins and zinc phosphate acting as anti-rust pigment for long term protection. For interior and exterior use. Cleaning and dilution with quick-drying solvent D-17 (Code 50.004).</p> <p><input type="checkbox"/> White (27.040) <input checked="" type="checkbox"/> Black* (27.045)</p> <p><input type="checkbox"/> Deep base/TR (27.055) New</p>	<p>This multipurpose bonding primer can be used as an impregnating and adhesion promoting primer for ferrous and non-ferrous metals, such as steel, aluminium, galvanized surfaces, PVC, glass, tiles and different wood materials such as wood panelling and trim (on wood - interior use only).</p> <p><i>APPROVAL CERTIFICATES: Fire retardant to B-s1,d0 standard (white only) - Certified for JUNO's protective anti-corrosive systems as per ISO 12944.</i></p> <p style="text-align: right;">15 l 4 l 750 ml</p> <p style="text-align: right;">NA</p>
<p>WORKSHOP Matt</p> 	<p>Quick-drying synthetic primer. A very quick drying synthetic primer formulated with iron oxides and alkyd resins. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p><input checked="" type="checkbox"/> Oxide red* (22.110) <input checked="" type="checkbox"/> Grey* (22.111)</p>	<p>Recommended for preparing iron surfaces both as a workshop primer for temporary protection and as a general purpose primer in fast drying alkyd-based systems for protection in mild to medium atmospheric corrosive environments.</p> <p style="text-align: right;">15 l 4 l 750 ml</p>
<p>WATERPRIM Matt</p> 	<p>Multi-surface waterbased anti-oxidant adhesion primer. Formulated with acrylic copolymers and anti-corrosive pigments of great durability. Unique in offering anti-corrosive properties. Contains low VOC levels and offers quick drying time. For interior and exterior applications. Cleaning and dilution with water.</p> <p><input type="checkbox"/> White (30.006)</p>	<p>Waterprim offers excellent adhesion on hard to paint interior and exterior substrates such as glossy surfaces, ceramic tiles, non-ferrous metal (such as aluminium, stainless steel and galvanised metal), vinyl, hardboard, melamine, varnish, plastic, GRP, UPVC, wood (interior use only), masonry and more.</p> <p><i>APPROVAL CERTIFICATES: Meets health related evaluation procedure for emissions of AgBB 2018 - A+ Certified.</i></p> <p style="text-align: right;">4 l 750 ml</p>

Wood primers


<p>HANGERS SEALER Matt</p> 	<p>High opacity synthetic wood primer/undercoat. A quick-dry primer and undercoat for most interior and exterior new or bare wood surfaces. Provides the best possible adhesion and evens up variable absorption, giving a uniform surface for the finishing system. For interior and exterior use.</p> <p><input type="checkbox"/> White (21.000)</p>	<p>Cleaning and dilution with white spirit D-16 (Code 50.012). Recommended for preparing wooden and masonry surfaces. Can also be used as finishing coats on interior surfaces. Ideal for softwood, plywood, chipboard flake board, MDF, etc.</p> <p style="text-align: right;">4 l 750 ml</p>
<p>NATURESELL Matt</p> 	<p>Quick dry water-based wood primer/undercoat. Naturesell is a water-based, high opacity, dual purpose primer undercoat for interior and exterior woodwork, Formulated with acrylic resins in aqueous dispersion with great resistance and high opacity. For interior and exterior use.</p> <p><input type="checkbox"/> White (21.100)</p>	<p>Cleaning and dilution with water. Ideal for use as a primer for softwoods, hardwoods, chipboard and fibre board.</p> <p style="text-align: right;">4 l 750 ml</p>














WOOD COATINGS

- _ Undercoat and preparation
- _ Water-based enamels
- _ Solvent-based enamels































Undercoat & preparation

<p>New</p> <p>SISKALTE UNDERCOAT</p> <p>Coming soon</p>	<p>Water-based anti-woodworm and fungicidal undercoat. Preventive and curative.</p> <p>Formulated with fungicidal and insecticidal additives in a propiconazole-free emulsion.</p> <p>Suitable for interior and exterior use.</p> <p>Cleaning and dilution with water.</p>	<p>Recommended for preventive and curative treatment against wood-boring beetles and termites. Suitable for preventive treatment against fungi that rot and stain wood. For use on both hardwood and softwood. Also used against fungi, mould, and other organisms that grow on construction materials such as stone and masonry.</p> <p style="text-align: right;">2,5 l 1 l</p>
<p><input type="checkbox"/> Clear (82.200) (Available in Spanish market only)</p>		
<p>AQUA BASE</p> <p><i>Matt</i></p> 	<p>Clear water-based wood preservative/undercoat for interior wood.</p> <p>Formulated with acrylic resins.</p> <p>For interior use.</p> <p>Cleaning and dilution with water.</p>	<p>Recommended as a sandable undercoat for all kinds of joinery including doors, windows and frames, parquet and other wood surfaces.</p> <p>Good filling power, easy application, quick drying and odourless. Valid treatment for both water based and synthetic topcoats.</p> <p style="text-align: right;">4 l 750 ml</p>
<p><input type="checkbox"/> Clear (82.414)</p>		

Water-based enamels

<p>AQUA VARNISH</p> <p><i>Gloss</i></p> 	<p>Special odourless water-based polyurethane varnish for parquet.</p> <p>Formulated with single component aliphatic polyurethane resins, providing a non-yellowing film with a high chemical resistance to wear.</p> <p>For interior use.</p> <p>Cleaning with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p>	<p>Recommended for all types of parquet and wood surfaces due to its ease of application. Quick drying, with high resistance to abrasion and easy cleaning. Preparation is recommended with Aqua Base undercoat (Code 82.414).</p> <p>Product not suitable for oak or chestnut wood due to darkening of the surface treated.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">4 l 750 ml</p>
<p><input type="checkbox"/> Clear (82.410)</p>		
<p>AQUADUR VARNISH</p> <p><i>Gloss / Satin / Matt</i></p> 	<p>Special water-based acrylic varnish for carpentry. Great hardness and chemical resistance.</p> <p>Formulated with acrylic resins, which provide a pleasant non-yellowing film.</p> <p>For interior use.</p> <p>Cleaning with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p>	<p>Recommended for any interior wood surfaces, especially furniture. Recommended primer: Aqua Base undercoat (Code 82.414). Product not suitable for oak or chestnut wood due to darkening of the surface treated.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of AgBB 2018 - A+ Certified - Fire retardant to C-s1,d0 standard.</i></p> <p style="text-align: right;">    4 l 750 ml </p>
<p><input type="checkbox"/> Clear / Gloss (82.480)</p>		
<p><input type="checkbox"/> Clear / Satin (82.481)</p>		
<p><input type="checkbox"/> Clear / Matt (82.482)</p>		
<p>LASUR ACUOSO</p> <p><i>Satin</i></p>  <p></p>	<p>Water-based woodstain with water-repellent properties. OPEN PORE protector with UV filters and anti-fungicidal protection.</p> <p>Formulated with acrylic resins, transparent pigments and fungicidal preservatives, which form a breathable, microporous, elastic, UV resistant film allowing moisture and air to be released.</p> <p>For interior and exterior use (clear woodstain for interior use only).</p> <p>Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p></p>	<p>Recommended for wooden surfaces exposed to weathering (wooden trim, doors, window frames, gates, fences, etc.). Does not crack or chip. Allows maintenance coats to be applied directly on to previous coats without need for removal. For interior use.</p> <p>For undercoat it is recommended to use Aqua Base (Code 82.414).</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">4 l 750 ml</p>
<p><input type="checkbox"/> Clear (82.451)</p>		
<p><input type="checkbox"/> Chestnu* (82.460)</p>		
<p><input type="checkbox"/> Oregon pine* (82.461)</p>		
<p><input type="checkbox"/> Oak* (82.462)</p>		
<p><input type="checkbox"/> Rustic oak* (82.463)</p>		
<p><input type="checkbox"/> Walnut* (82.464)</p>		
<p><input type="checkbox"/> Mahogany* (82.465)</p>		
<p><input type="checkbox"/> Rosewood* (82.466)</p>		
<p><input type="checkbox"/> Teak* (82.467)</p>		
<p><input type="checkbox"/> Iroko* (82.468)</p>		

Solvent-based enamels








<p>JUNODUR VARNISH Gloss / Satin</p> 	<p>Special synthetic polyurethane varnish for parquet. Hardness and resistance to domestic use. Formulated with urethane resins to obtain a protective, decorative finish, which is pleasant to the touch. For interior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Clear / Gloss (44.001)</p> <p><input type="checkbox"/> Clear / Satin (44.002)</p>	<p>Recommended for restoring and varnishing parquet and wooden floors that require a hard surface which is resistant to domestic use and neutral cleaning products.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">4 l 750 ml</p>									
<p>JUNOLAC VARNISH Gloss / Satin / Matt</p> 	<p>Synthetic clear varnish with UV filters. Highlights wood's natural tones. Formulated with alkyd resins and ultraviolet filters for a protective and decorative finish. For interior use. Gloss finish also for exterior use. Cleaning and dilution with mineral white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Clear / Gloss (42.037)</p> <p><input type="checkbox"/> Clear / Satin (42.038)</p> <p><input type="checkbox"/> Clear / Matt (42.039)</p>	<p>Recommended for decorating and protecting wood surfaces such as window frames, doors, trim, furniture, etc.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">4 l 750 ml 375 ml</p>									
<p>JUNOTINTE VARNISH Gloss</p>  <p></p>	<p>Synthetic coloured varnish with UV filters. For colourful and decorative finish. Formulated with alkyd resins and ultraviolet filters for a protective and decorative finish. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p>i</p> <table border="0"> <tr> <td> Pine* (42.040)</td> <td> Chestnut* (42.043)</td> <td> Rosewood* (42.045)</td> </tr> <tr> <td> Walnut* (42.041)</td> <td> Teak* (42.044)</td> <td> Oak* (42.046)</td> </tr> <tr> <td> Mahogany* (42.042)</td> <td></td> <td></td> </tr> </table>	 Pine* (42.040)	 Chestnut* (42.043)	 Rosewood* (42.045)	 Walnut* (42.041)	 Teak* (42.044)	 Oak* (42.046)	 Mahogany* (42.042)			<p>Recommended for decorating and protecting wood surfaces such as window frames, doors, trim, furniture, etc</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">i 750 ml 375 ml</p>
 Pine* (42.040)	 Chestnut* (42.043)	 Rosewood* (42.045)									
 Walnut* (42.041)	 Teak* (42.044)	 Oak* (42.046)									
 Mahogany* (42.042)											
<p>YACHT VARNISH Gloss</p> 	<p>Synthetic high build full gloss varnish with UV filters. Special for harsh weather conditions. Formulated with alkyd resins of great flexibility and ultraviolet filters for a protective, decorative and highly durable finish of the highest quality. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Clear (42.036)</p>	<p>Recommended and suitable for hard and softwood subjected to harsh weather conditions humidity, salinity and solar exposure.</p> <p>Contains UV filters which protect against strong sunlight.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">4 l 750 ml</p>									







SUNDRIES


- _ Fillers & caulk
- _ Colourants, paint stripper, additives, etc
- _ Thinners & cleaners
- _ Colour charts & fan decks






Fillers & caulk

<p>JUNO FILLER <i>For preparation work</i></p> 	<p>Shrink & crack resistant filler for interior repairs. Removes small imperfections, grooves, cracks, etc. Theoretical performance: 1 m²/kg/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White powder. For interior use. Smooth finish.</p> <p style="text-align: right;">15 kg 5 kg 1 kg</p> <hr/> <input type="checkbox"/> White (77.000)
<p>READY MIX FILLER <i>For repairs</i></p> 	<p>Tintable ready mix repair filler. Smooth ready to use finish filler with excellent adhesion. Theoretical performance: 1.75 kg/m²/mm thickness. Max. thickness per layer: 2 mm.</p>	<p>Ready mix filler that can be coloured using JUNO universal colourants (max. 3%). For interior use. Smooth, very fine finish.</p> <p style="text-align: right;">5 kg 1 kg 500 gr.</p> <hr/> <input type="checkbox"/> White (77.200)
<p>SMOOTH FINISH FILLER <i>For finishing</i></p> 	<p>High performance interior finishing filler. For smoothing and levelling walls before painting or wallpapering. Theoretical performance: 1 m²/kg/mm thickness. Max. thickness per layer: 2 mm.</p>	<p>White powder. For interior use. Smooth finish.</p> <p style="text-align: right;">15 kg</p> <hr/> <input type="checkbox"/> White (77.030)
<p>SANDABLE FILLER <i>For renovations</i></p> 	<p>Easy-to-sand interior renovation filler Formulated to mix into a smooth consistency for easy application. Theoretical performance: 0.950 kg/m²/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White, easy-to-sand powder filler. For interior use. Smooth finish.</p> <p style="text-align: right;">15 kg</p> <hr/> <input type="checkbox"/> White (77.410)
<p>COVER ALL FILLER <i>For renovations</i></p> 	<p>Skimcoat filler for renovations. Smooths and levels textured decorative surfaces. Theoretical performance: 1 m²/kg/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White powder with good adhesion. For interior use. Smooth finish.</p> <p style="text-align: right;">15 kg</p> <hr/> <input type="checkbox"/> White (77.406)
<p>RAPID FILLER <i>For repairs</i></p> 	<p>A quick-set cement filler for repairs. A high performance quick drying filler for repairs of any masonry surfaces. For skimming surfaces in fine layers, up to 6 mm. Theoretical performance: 1.5 kg/m²/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White powder. For interior/exterior use. Fine and very hard finish.</p> <p style="text-align: right;">15 kg 5 kg</p> <hr/> <input type="checkbox"/> White (77.301)
<p>QUICK DRYING REPAIR MORTAR <i>For repairs</i></p> 	<p>White powder cement mortar specially designed for repairing, filling and rendering exterior surfaces. Quick set, great filling capacity and excellent adhesion. Easy application. Max. thickness/coat: 5 mm for wall; For repairs no thickness limit.</p>	<p>Practical coverage: 1,23 Kg/m² White powder. Exterior use.</p> <p style="text-align: right;">15 kg</p> <hr/> <input type="checkbox"/> White (77.305)

<p>MULTI-PURPOSE FILLER <i>Repair</i></p> 	<p>Powdered mortar for repairing, rebuilding or joining any surface. Suitable for humid environments such as bathrooms, kitchens, etc. Joins materials of different nature and/or absorption level. Direct application on ceramics. Theoretical performance: 1 kg/m²/mm. Thickness per layer: any thickness.</p> <p><input type="checkbox"/> White (77.050)</p>	<p>White powder. For interior/exterior use. Quick-drying.</p> <p style="text-align: right;">5 kg 1 kg</p>
<p>FIBRE enriched FILLER <i>For reinforcement</i></p> 	<p>Ready to use, flexible, fibre reinforced exterior/interior filler. For sealing and reinforcing dynamic cracks and fissures on plaster, concrete, etc. Does not crack or split, has high adhesion and permanent elasticity. Can be painted on, except with solvent based 2-component products. Theoretical performance: 1,2 kg/m²/mm.</p> <p><input type="checkbox"/> Light grey (77.250)</p>	<p>Recommended thickness per layer: 0.3 to 3 mm. Light grey paste. For interior/exterior use.</p> <p style="text-align: right;">4 l 750 ml</p>
<p>ANTI-CONDENSATION FILLER <i>Thermal insulation</i></p> 	<p>Light anti-condensation filler for interior use: For smoothening, renewing and filling interior surfaces. Avoids "cold wall effect" and offers thermal and acoustic insulation. Great performance and filling capacity. Excellent adhesion properties. Interior use.</p> <p><input type="checkbox"/> Light grey (77.302)</p>	<p>Before application eliminate and clean mould from surfaces with Junoclean (Code 760.180). Layer thickness: any thickness. Working time: 2 hours. Theoretical performance: 0.6kg/m² Grey powder.</p> <p style="text-align: right;">10 kg</p>
<p>MRT-100 <i>Bonding & rendering</i></p> 	<p>Mortar for bonding and rendering thermal insulation boards. Fibre reinforced and flexible cement based mortar used for the application of various types of thermal insulating boards such as EPS, XPS and MW. Fibre reinforced. Excellent adhesion. High permeability to water vapour and high impact resistance.</p> <p><input type="checkbox"/> White (77.600)</p>	<p>Practical coverage - bonding: 3,5-4,5 kg/m² Practical coverage - rendering: 4-5 kg/m² for 3-5 mm thickness. White powder. Use interior/exterior. Part of the External Thermal Insulation Composite System (ETICS) JUNOTherm®.</p> <p style="text-align: right;">25 kg</p>

Colourants, paint stripper, additives, etc

<p>COLOURANT</p> 	<p>Universal concentrated colourant. For interior and exterior use. Note: Vermilion red and Lemon yellow colourants are for interior use only.</p> <p><input type="checkbox"/> Lemon yellow* (79.404) <input type="checkbox"/> Black* (79.400) <input type="checkbox"/> Ochre yellow* (79.406) <input type="checkbox"/> Vermilion red* (79.402)</p> <p><input type="checkbox"/> Blue* (79.401) <input type="checkbox"/> Oxide red* (79.403) <input type="checkbox"/> Shadow brown* (79.407) <input type="checkbox"/> Green* (79.405)</p>	<p>Recommended for colouring all kinds of paint. The proportion of colourant in the paint should not exceed 3%.</p> <p style="text-align: right;">1 l 100 ml</p> <p style="text-align: right;">NA</p>
---	---	--

<p>JUNO PAINT STRIPPER</p> 	<p>High performance, quick action paint stripper. Formulated with special solvents, free of methylene chloride. For interior and exterior use.</p>	<p>Recommended for quickly and conveniently removing most paints, enamels and varnishes. Its action is based on penetration between the paint film and the substrate, breaking the adhesion between both.</p>
		4 l 750 ml 375 ml
		<input checked="" type="checkbox"/> Clear (83.100)
<p>MISKY-MISKY <i>Fungicidal additive</i></p> 	<p>Fungicidal concentrate to protect decorative finishes from future mould attack. Formulated with heterocyclics, developing an intense prolonged broad spectrum action against moulds and algae. Add at least one (100 ml) bottle to 15 litres of paint and stir or shake until product has been distributed and mixed evenly with the paint.</p>	<p>Recommended as an additive to be mixed into emulsion paint, primer, undercoat, varnish, gloss, wallpaper paste, textured paint or tile adhesive to prevent the formation of mould.</p>
		100 ml
		<input type="checkbox"/> White (79.597)
<p>ANTI-SLIP MICROBEADS</p> 	<p>Anti-slip microbeads for floor coatings. Polypropylene microbeads with average diameter of 180 microns to improve the slip resistance of floor surfaces particularly when wet. Add a 150 gram tub for every 4L of paint, and 4 tubs for every 15 L of paint to achieve certified anti-slip protection.</p>	<p>This product gives the following product range from JUNO Class 3 Anti-slip rating: Dynapok agua Floor Epoxy (07.1....), Dynamol (09.5....), Junosol (06.1....), Pavimyc (07.8....), Junoretano (88.8....), and Junopoxi (88.8....).</p>
		150 gr
		<input type="checkbox"/> White (07.250)
<p>MICROBEADS FOR PAVIMYC HB 2/C</p> 	<p>Anti-slip microbeads for epoxy high-build floor coating systems. Polyethylene microbeads with an average diameter of 250 microns suitable for obtaining non-slip properties on wet surfaces.</p>	<p>Recommended as an anti-slip additive to obtain class 3 slip resistance in Pavimyc HB 2/C systems. Add a can of 400 grams for every 20 kg of paint.</p>
		400 gr
		<input type="checkbox"/> White (07.251)
<p>JUNOCLEAN</p> 	<p>JUNOCLEAN cleans interior and exterior mould and mildew stains fast. Sprayable for easy application. For interior and exterior use. Cleans stains fast and efficiently.</p>	<p>Ideal for use on masonry, brick, tiles, vinyl siding, wood, grout or other materials. Also ideal for kitchens, bathrooms and other spaces where organic dirt, mould and humidity is a problem. Available in larger packs upon request. Ask in-store for more information.</p>
		500 ml
		<input checked="" type="checkbox"/> Clear (760.180)

Thinners & cleaners

		20 l	5 l	1 l	500 ml
D-16 <i>White spirit</i>	Mineral thinner for synthetic products. Code (50.012)				
D-17 <i>Quick drying</i>	Thinner for synthetic enamels and primers. Code (50.004)				NA
D-40 <i>Chlorinated rubber</i>	Thinner for chlorinated rubber and pliolite enamels. Code (50.000)				NA
D-45 <i>Universal</i>	Universal thinner. Code (50.017)				NA
D-47 <i>Multi-purpose</i>	Thinner for professional use (cleaning). Code (50.019)			NA	NA
D-69 <i>Odourless</i>	Thinner for odourless stain block. Code (50.073)	NA			NA
D-70 <i>Polyurethane</i>	Thinner for polyurethane enamels and varnishes. Code (50.007)				NA
D-71 <i>PU Retardant</i>	Retardant for Polyurethane enamels and varnishes. Code (50.014)				NA
D-75 <i>Retardant</i>	Retardant Thinner. Code (50.107)	NA			NA
D-90 <i>Epoxy</i>	Thinner for epoxy enamels. Code (50.010)				NA

Colour charts & fan decks













		1 Unit.
NCS	NCS 980 - JUNO colour selection fan deck (Code. 999.651)	
RAL	RAL - JUNO colour selection fan deck (Code. 999.631)	
JUNO COMBINA	COMBINA FAN DECK (Code. 999.650) COMBINA COLOUR CARD (Code. 999.632) POS RETAIL COMBINA COLOURS STAND (Code. 999.667)	
EXTERIOR FAÇADES	FAÇADE COLOURS FAN DECK (Code. 999.675) FAÇADE COLOURS COLOUR CARD (Code. 999.628) POS RETAIL FAÇADES COLOUR STAND (Code. 999.666)	
COLOUR CARDS	JUNO colour cards JUNOKRIL Colour Card (999.636) BIKRIL / LUNA Colour Card (999.620) JUNOREV CHART (999.626) JUNOTINTE Colour Card (999.623) FLOOR RANGE (999.635) LASUR Colour Card (999.624) JUNOLAC ANTI-OX Colour CARD (999.625) OXIFORJA Colour Card (999.629) JUNOPLUS Colour Card (999.627) JUNODECO Colour Card (999.724) WATERPROOFING Colour Card (999.721)	1 Unit.

SUPPLEMENTARY PRODUCTS




- _ Special exterior coatings
- _ Special interior coatings
- _ Water-based 2K Polyurethane
- _ Sealers/primers
- _ Thinners
- _ Varnish
- _ Colourants - Tinting System

Special exterior coatings


Water-based

<p>SILOX Matt</p> 	<p>Siloxane-based paint with excellent resistance to weathering. With anti-mould protection. Paint with polysiloxane resins that provide high hydrophobicity. For exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (62.005)</p>	<p>Recommended for painting and decorating façades where a matt finish is required. Resistant to rain water, permeable to water vapour and resistant to ultraviolet rays and the formation of mould.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p></p> <p>15 l</p>
<p>JAKRILEN A-50 Matt</p> 	<p>High performance water-based paint. With anti-mould protection. Formulated with acrylic copolymers in aqueous dispersion. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (62.500)</p>	<p>Recommended for all types of constructions and ornaments.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p></p> <p>15 l 4 l</p>
<p>JUNOSIL SILICONE BASED PLASTIC PAINT Matt</p> 	<p>Silicone water-based paint. Paint with acrylic copolymers and silicone additives. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (73.160)</p>	<p>Particularly recommended for painting and decorating surfaces coated with lime renders thanks to its excellent whiteness and opacity.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p></p> <p>15 l</p>
<p>A-4000 Matt</p> 	<p>Water-based paint. Formulated with copolymers in aqueous emulsion, with an anti-dust effect and matt finish. For interior and protected exterior use. Cleaning and dilution with water.</p> <p>  Product subject to availability. Variations in colours between batches may occur.</p> <p><input type="checkbox"/> Grey* (62.512)</p>	<p>Recommended for walls, bridges, tunnels, warehouses or car parks where a quality matt finish is required.</p> <p>15 l</p>

Masonry coating


<p>MEDITERRANEAN FAÇADES Matt</p> 	<p>High-build water-based masonry coating. Formulated with acrylic-styrene copolymers. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (73.312)</p>	<p>Recommended for use outdoors in mild climates and for decorating and for decorating interior warehouses, staircases, garages and places where a high build finish is required.</p> <p>Allows for fine stippling interior spaces.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p></p> <p>15 l</p>
--	---	--

Pliolite paint

<p>HYDROPLIOLITE Matt</p> 	<p>High quality water-based pliolite paint. Alkali resistant and contains anti-mould preservatives. Formulated with pliolite resins in aqueous dispersion. Providing excellent adhesion to degraded substrates, and excellent resistance to alkalis and UV rays. Interior and exterior use. Cleaning and dilution with water.</p> <p><input type="checkbox"/> White (62.991)</p>	<p>Recommended for protection of exterior walls, partition walls and concrete surfaces in general, where good adhesion, a matt finish and great resistance to atmospheric agents is required.</p> <p style="text-align: right;">15 l</p>
--	---	--

Special interior coatings

Specialty paints

<p>J-35 EXTRA MATT Extra-matt</p> 	<p>Extra-matt emulsion with added opacity. With anti-mould protection. Formulated with acrylic copolymers with extra-matt finish. High quality, no splash application, and excellent levelling properties. Great washability. For interior use. Cleaning and dilution with water.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (72.205)</p>	<p>Ideal for ceilings, workshops, warehouses, hallways, and large spaces where a completely matted finish is required.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l</p>
<p>B-7 BLACK Matt</p> 	<p>High quality water-based emulsion. Formulated with acrylic copolymers and selected black pigments that provide a deep black finish. For interior use. Cleaning and dilution with water.</p> <p> Black* (72.101)</p>	<p>Recommended for decorating homes, designer spaces, etc. Provides excellent hiding power and is very resistant to wet rubbing and scuffing.</p> <p><i>APPROVAL CERTIFICATES: Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l 4 l</p>
<p>COVERFIX Matt</p> 	<p>Elastomeric matt paint special for joints and cracks. Formulated with acrylic copolymers and elastomeric resins for withstanding movements in weak and exposed surfaces such as plaster, gypsum, etc. Great filling power, and good coverage. Matt crack-bridging finish that conceals joints and splices. For interior use. Cleaning and dilution with water.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (62.875)</p>	<p>Designed to withstand movement on plaster, gypsum and filler surfaces which are prone to cracking with time. Ideal to go over new-builds before handover.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;">15 l</p>

Water-based 2K polyurethane

AQUAPUR 2/C

Gloss / Satin



Two-pack water-based polyurethane coating.

Formulated based on polyurethane resins offering hard and resistant surfaces. Excellent levelling and resistance to rubbing. Robust weather resistant finish for exterior use.

Good flexibility and easy application.

Quick drying.

Interior and exterior use.

Cleaning and dilution with water.



For use on properly primed wood and metal surfaces. Recommended for all types of surfaces, especially wood carpentry such as kitchens, doors, window trims, skirting boards, etc. and for perfect smooth finishes on walls.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified - Fire retardant to B-s1,d0 standard.



4 l

White / Gloss (08.310)

White / Satin (08.315)

Sealers/primers

Sealers

QUICK DRYING STAIN BLOCK

Matt



Synthetic matt stain block with special resins.

Interior use.

Cleaning and dilution with Universal thinner D-45 (Code 50.017).

Recommended for all types of surfaces that have damp, grease, nicotine or other stains, or surfaces that have lost their hue. May be used as a quick drying primer for porous substrates or as a sealer/stain blocker. Seals porous surfaces with excellent enamel holdout.

15 l

4 l

750 ml

White (21.380)

Synthetic primer

“R” PRIMER

Matt



Economic synthetic primer.

Formulated with alkyd resins and iron oxides providing high opacity.

For interior and exterior use.

Cleaning and dilution with “Dilution for “R” primer” (Code 50.090).

Recommended for preparing ferrous surfaces, where an economic paint system is required.



Product subject to availability. Possibility of difference in colour/sheen between production batches.

15 l

4 l

Grey* (22.119)

Thinners

DILUTION FOR “R” PRIMER

Dilution for “R” primer and cleaner thinner for synthetic products.





Product subject to availability.

20 l

5 l



Code (50.090)

2K Clear polyurethanes

<p>2K GRAF COATING Gloss / Satin / Matt</p> 	<p>Two-pack clear aliphatic polyurethane gloss coating. Cleaning and dilution with Polyurethane Thinner D-70 (Code 50.007). For interior and exterior use.</p> <p>EPD THE INTERNATIONAL EPD SYSTEM</p> <p><input checked="" type="checkbox"/> Clear / Gloss (44.270) <input checked="" type="checkbox"/> Clear / Satin (44.271)</p> <p><input checked="" type="checkbox"/> Clear / Matt (44.272) New</p>	<p>Recommended for facilitating the removal of graffiti by cleaning. Other uses: coating indoor concrete floors, coating metal surfaces and for those places where a high quality gloss finish is required.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">4 </p>
<p>AQUAPUR PU VARNISH 2/C Gloss / Satin / Matt</p> 	<p>Two-pack water-based polyurethane varnish. Provides a tough clear film finish with great chemical and wear/abrasion resistance and easy cleaning. Great hardness. Quick drying. Easy application. Interior use. Cleaning and thinning with water.</p> <p><input checked="" type="checkbox"/> Clear / Gloss (82.485)</p> <p><input checked="" type="checkbox"/> Clear / Satin (82.486)</p> <p><input checked="" type="checkbox"/> Clear / Matt (82.487)</p>	<p>Recommended for all types of parquet and wooden surfaces. Also indicated as sealing and protection layer on 100% solids epoxy systems. (PAVIMYC HB flooring systems).</p> <p style="text-align: right;">4 </p>

Colourants - Tinting System

Colourants for Tinting System

<p>JUNOMATIC Colorant</p>   <p>JUNOMATIC Tinting System</p>	<p>Colourants for JUNO's Tintometric System.</p> <p>Decorative Tintometric System</p> <p>! Colourants for JUNOMALTE and JUNOPROF bases 1 </p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> JS / Black (88.700) <input checked="" type="checkbox"/> LS / Blue (88.701) <input checked="" type="checkbox"/> MS / Yellow (88.702) <input checked="" type="checkbox"/> NS / Red (88.703) <input checked="" type="checkbox"/> PS / Green (88.704) <input checked="" type="checkbox"/> QS / Intense yellow (88.705) <input checked="" type="checkbox"/> RS / Intense blue (88.706) <input checked="" type="checkbox"/> TS / Oxide ochre (88.707) <input checked="" type="checkbox"/> US / Orange (88.708) <input checked="" type="checkbox"/> VS / Intense red (88.709) <input checked="" type="checkbox"/> WS / Oxide brown (88.710) <input checked="" type="checkbox"/> XS / Grey (88.711) <input checked="" type="checkbox"/> YS / Oxide red (88.712) <input checked="" type="checkbox"/> ZS / Violet (88.713) <input checked="" type="checkbox"/> KU / Oxide white (88.714) <input checked="" type="checkbox"/> BS / Magenta (88.715) <p>! Special colourants for exterior coatings 1 </p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> HS (88.716) <input checked="" type="checkbox"/> IS (88.717) <input checked="" type="checkbox"/> GS (88.718) 	<p>Industrial Tintometric System</p> <p>! Colourants for JUNORAPID, JUNOPOXI and JUNORETANO bases 1 </p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> TBF / White (88.975) <input checked="" type="checkbox"/> TAM / Oxide yellow (88.979) <input checked="" type="checkbox"/> TEF / Oxide red (88.980) <input checked="" type="checkbox"/> TAF / Medium yellow (88.986) <input checked="" type="checkbox"/> TNA / Orange (89.980) <input checked="" type="checkbox"/> TRO / Organic red (89.981) <input checked="" type="checkbox"/> TUL / Blue (89.982) <input checked="" type="checkbox"/> TVE / Green (89.983) <input checked="" type="checkbox"/> TNG / Black (89.984) <input checked="" type="checkbox"/> TMG / Magenta (89.985) <input checked="" type="checkbox"/> TLL / Medium yellow (89.987)
---	--	--







Mar
ke

**MARKETED
PRODUCT RANGE**







- _ Intumescent paints
- _ Waterproofing: Liquid polyurethane membrane

Pro
ducts

Intumescent paints

<p>WIP PROMAPAIN SC3/SC4 <i>Matt</i></p> 	<p>Water-based reactive fire protective coating. Intumescent paint for fire protection of steel structures.</p> <p>Reacts in the presence of and in contact with flames, forming an insulating foam, giving off salts with a fire fighting action.</p> <p>For interior and exterior use. In exterior use finish with a proper paint</p> <p>Product ready to use, do not dilute.</p> <p>Cleaning with water.</p>	<p>Recommended for application on beams and open and closed metal sections, to provide a delay to the spread of fire of 30, 60, 90 or 120 minutes depending on the mass and microns applied.</p> <p style="text-align: right;"> AFITI LICOF</p> <p style="text-align: right;">25 kg</p> <p><input type="checkbox"/> SC3 / White (89.053) <input type="checkbox"/> SC4 / White (89.054)</p>
<p>NULLIFIRE <i>Matt</i></p> 	<p>Water-based insulating intumescent paint, with a high resistance to fire.</p> <p>Reacts in the presence of and in contact with flames, forming an insulating intumescence, giving off salts with a fire fighting action, preventing an easy ignition of combustible materials and delaying the destruction of metal structures, maintaining their mechanical properties.</p> <p>For interior and exterior use. In exterior use finish with a proper paint</p> <p>Product ready to use, do not dilute.</p>	<p>Cleaning with water.</p> <p>Recommended for application on beams and open, closed or gapped metal sections, to provide a delay to the spread of fire depending on the mass and microns applied.</p> <p style="text-align: right;"> AFITI LICOF  Applus®  ENOV</p> <p style="text-align: right;">25 kg</p> <p><input type="checkbox"/> SC803-90 / White (89.070)</p>

Liquid polyurethane membrane

<p>JUNOPRIMERE-LASTIC H 2/C <i>Gloss</i></p> 	<p>2-component water based epoxy primer for liquid polyurethane membrane waterproofing system</p> <p>For interior and exterior use.</p> <p>Cleaning and dilution with water.</p>	<p>Recommended for the application of Junoelastic-K polyurethane membrane on a variety of surfaces (terraces, decking, tanks, flooring permanently exposed to humidity, etc.) or for flooring on a medium with humidity of between 4% and 10%.</p> <p style="text-align: right;">18 kg 5 kg</p> <p><input checked="" type="checkbox"/> Clear (95.509)</p>
<p>JUNOELASTIC-K (ST) <i>Semi-matt</i></p> 	<p>One component liquid waterproof aromatic polyurethane membrane.</p> <p>For interior and exterior use. When used on exterior, finish with Elastipur (Code 95.525).</p> <p>Dilution with solvent D-17 (Code 50.004).</p>	<p>Recommended for outdoor surfaces such as flat roofs and balconies. Also suitable for tanks, concrete surfaces, green roofs, flower beds, damp indoor areas (bathrooms, kitchens, etc.). Forms a uniform, elastic, waterproof, vapor-permeable sealing layer, without forming seams or joints. Excellent mechanical, chemical, thermal, UV and weather resistance properties.</p> <p style="text-align: right;">25 kg</p> <p><input checked="" type="checkbox"/>  Grey* (95.542) <input checked="" type="checkbox"/>  Tile* (95.543) <input checked="" type="checkbox"/>  Red* (95.544)</p>
<p>ELASTIPUR <i>Gloss</i></p> 	<p>High performance, single component, aliphatic polyurethane resin sealer.</p> <p>For interior and exterior use.</p> <p>Dilution with solvent D-17 (Code 50.004).</p> <p>Resistant to abrasion and wear and UV radiation.</p>	<p>Recommended as a finishing coat for the Junoelastic-K (ST) polyurethane membrane waterproofing system.</p> <p style="text-align: right;">20 kg 4 kg</p> <p><input checked="" type="checkbox"/> Clear (95.525)</p>



PAINT MANUFACTURERS SINCE 1927



JUNO PAINTS LTD.
Unit 1, Zone 5 Clonminam Business
Park Portlaoise, Co. Laois
R32W2RW
Phone: (+353) 057 867 0634
info@junopaints.ie
www.junopaints.ie

JUNO PAINTS CENTRAL HQ
Barrio Saconi, 10
48950 Erandio (Bizkaia) SPAIN
Tel.: +34 944 670 062 - Fax: +34 944 675 832
infoweb@juno.es
www.junopaints.com
www.juno.es

