

# Technical Datasheet

## Mineral White Spirit D-16



Product Code: 50012 Thinner/cleaner

### DESCRIPTION

**Mineral diluent for synthetic products. Formulated based on a mixture of aliphatic hydrocarbons.**

### USE

Recommended for dilution and cleaning of enamels and synthetic primers. Use only with products where it is recommended to use D-16 in the technical data sheet.

### PROPERTIES

- Adequate evaporation speed that allows a uniform finish.
- Perfect balance between internal and superficial drying
- Adjusts the viscosity in the indicated paints
- High cleaning and dissolving power

**Colour:** Clear

**Density:** 0,78 ± 0,05 g/cc S/FR1001/D

**Flashpoint:** Flammable (39 °C)

50012 CLEAR



Format: 0,5 / 1 / 5 / 20 L

### SURFACE PREPARATION

Proceed as indicated for the paint products where this thinner is recommended.

### INDICATIONS OF USE

**THINNER.** Add the recommended amount according to the technical data sheet of the product to be diluted. Stir the mixture slowly until completely homogeneous.

**CLEANING.** Clean tools immediately after use to prevent paint from drying out. Thoroughly remove any traces of paint and then wash the material with soapy water. Let the tools and cleaned material dry completely.

### SAFETY AND ENVIRONMENT

As this is a solvent based product, it must be applied with good air circulation and with the necessary protection measures. Avoid sources of ignition. Minimize product waste by estimating the correct amount needed, taking into account the m<sup>2</sup>, porosity and texture of the surface. Store any excess material (unmixed) in a ventilated and dry place. The container must be clean and of adequate size for the amount of product left over. Close containers carefully and keep upright to avoid spills. Preserve the containers of frost, high temperatures and direct exposure to the sun. Keep any unused product for later use to reduce environmental effects. Do not eat, drink or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures. For more information, consult the Safety Data Sheet. In case of contact with eyes wash with clean and abundant water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose of at an authorized waste collection point. Consult your local city council about the correct recycling of both the container and waste and leftovers of paint according to law and principles of environmental respect.

The information contained in this data sheet may change and must be updated. Consult [www.juno.es](http://www.juno.es) or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions. Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (Spain) • Tel.: +34 944 670 062 • [infoweb@juno.es](mailto:infoweb@juno.es) • [www.junopaints.com](http://www.junopaints.com)